

Search Results

Evaluate

- Advertisements
- PDFQuickNet Cab
- FAQ's
- Technical References
- PDFMaintaining ..
- White Papers
- PDFBest Practic ..

Design a Solution

- Best Practices
- PDFVisual Inspe ..
- Specification Sheets
- PDFQuickNet MTP ..

How to Buy

- Bill of Material
- Favorite Products List
- Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips  Within Results


 Text Search: 'F612D5-5M8Y'

Your search criteria matched only one product, shown below

F612D5-5M8Y



- Pass all TIA/EIA-568-B.3 performance requirements
 - FOCIS-5 compliant
 - Insertion loss per mated pair: .50dB typical; .75dB max.
 - Factory terminated, assembled and 100% tested for insertion loss
 - Insertion loss data recorded for every multimode cable assembly
 - Lifetime traceability of test data to a Q.C. number on each cable assembly
 - 2-pin alignment assures consistent repeatable performance
- * MTP is a registered trademark of US Conec Ltd.

Part Number	F612D5-5M8Y
RoHS Compliancy Status	Compliant
Note	F612D5-5M8Y replaces F612D5-5M8
Part Description	Female MTP* to female MTP* twelve strand fiber optic cable assembly (one female MTP* connector on each end on ribbon inerconnect cable) – 62.5/125m.
Product Type	MTP* 12 Fiber Interconnect Cable Assemblies
Length (m)	8
Fiber Compatibility	62.5/125m
Fiber Type	Multimode
Connector 1 Type	MTP* Connector
Connector 2 Type	MTP* Connector
End Configurations	MTP* to MTP*
Fiber Count	12
Flammability Rating	Plenum (OFNP)
Pricing Description	MTP* MTP* Interconnect Cable Assembly 8m 62.5 m
Min. Order UOM	PC
Min. Order Qty.	1
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.