


THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

| PANDUIT PART NUMBER | FIBER TYPE | JACKET RATING | DIAMETER | BEND RADIUS | |
|---------------------|---------------------------|---------------|-------------------|------------------|------------------|
| | | | | INSTALLED | LONG TERM |
| FSPR936Y | SINGLEMODE 9/125µM | OFCR | 24.4mm [0.961"] | 55.3cm [21.8"] | 27.7cm [10.9"] |
| FSP936Y | | OFCP | | | |
| FSPL936Y | | OFCR-LS | 21.3mm [0.839"] | | |
| FSPR536Y | MULTIMODE 50/125µM | OFCR | 24.4mm [0.961"] | | |
| FSP536Y | | OFCP | | | |
| FSPL536Y | | OFCR-LS | 21.3mm [0.839"] | | |
| FSPR636Y | MULTIMODE 62.5/125µM | OFCR | 24.4mm [0.961"] | | |
| FSP636Y | | OFCP | | | |
| FSPL636Y | | OFCR-LS | 21.3mm [0.839"] | | |
| FOPRX36Y | MULTIMODE 50/125µM OM3 | OFCR | 24.4mm [0.961"] | | |
| FOPP36Y | | OFCP | | | |
| FOPL36Y | | OFCR-LS | 21.3mm [0.839"] | | |
| FOPRZ36Y | MULTIMODE 50/125µM OM4 | OFCR | 24.4mm [0.961"] | | |
| FOPP36Y | | OFCP | | | |

| FIBER OPTIC 36 FIBER ARMORED DISTRIBUTION CABLE WITH 3 SUB-UNITS OF 12 FIBERS CUSTOMER DRAWING | | | | | | | | | |
|--|------|----|-----|-------------|--|---|-------------------------------|-----|-----------|
|  PANDUIT ™ CORP. TINLEY PARK, ILL 60477 | | | | | | | | | |
| <p>ALL DIMENSIONS ARE GIVEN IN INCHES, UNLESS OTHERWISE SPECIFIED.</p> <p>DIMENSIONAL TOLERANCES ARE: (.X) ±0.3 (.010) (.XX) ±0.8 (.03) ANGLES</p> | | | | | | | | | |
| | | | | | DRAWING FILENAME M02055BV_DC_36/01A | | SCALE NONE | | |
| | | | | | DRAWN BY MC | | REVIEW DRAWING NUMBERS | | |
| | | | | | DATE 02-28-06 | | PART NO. FSP**36Y FOP**36Y | | |
| 02 10-26-09 EFK RELEASED TO PRODUCTION 02055-105 | | | | | CHK'D WMA | | DRAWING NO. 02055-105 | | SIZE A |
| REV | DATE | BY | CHK | DESCRIPTION | ECN | R | CUST | SUP | OTH |