


Search Results

- Evaluate
 - FAQ's
- Design a Solution
 - Catalog Cut Sheet
 - PDFHST0.4-3-Q2Y
 - Part Drawings
 - PDFThick Wall P..
 - Specification Sheets
 - PDFThick Wall P..
- How to Buy
 - Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips

 Text Search: 'HST2.0-48-2Y'

Your search criteria matched only one product, shown below

HST2.0-48-2Y



- Shrink ratio of 3:1 insulates a wide range of diameters and irregular shapes, which reduces inventory costs
 - Cross-linked, UV resistant material improves flame retardancy, chemical, and temperature resistance
 - Thick wall product seals and insulates in one step to speed installation
 - Meets Mil Spec AMS-DTL-23053/15 Class 1
- * For red, add 2 to end of part number package suffix (Example HST0.4 -3-Q2).

Part Number	HST2.0-48-2Y
RoHS Compliancy Status	Compliant
Note	HST2.0-48-2Y replaces HST2.0-48-2
Part Description	Thick Wall Heat Shrink provides excellent protection above or below ground level and is suitable for wet locations and direct burial (UL486D)
Material	Highly flame retardant adhesive lined cross-linked polyolefin
Color	Black
CSA Certified	Yes
Military Specification	AMS-DTL-23053/15 Class 1
UL Listed	Yes
UL Recognized	Yes
Length (In.)	48.0
Length (mm)	1219.2
Copper Conductor Size Range	#250 MCM– #750 MCM
CE Compliant	No
Conductor Size Range (mm)	240 – 500
Flammability Rating	VW-1
Max. Connector O.D. (In.)	1.600
Max. Connector O.D. (mm)	40.6
Max. Recovered I.D. (In.)	0.67
Max. Recovered I.D. (mm)	16.9
Min. Cable O.D. (In.)	0.750
Min. Cable O.D. (mm)	19.1
Min. Expanded I.D. (In.)	2.00
Min. Expanded I.D. (mm)	50.8
Nominal Recovered Wall Thickness (In.)	0.16
Nominal Recovered Wall Thickness (mm)	4.1
Pricing Description	Heat Shrink Thick Adhesive, 2(50.8mm) Dia, Black
Shrink Ratio	3:1
Temperature Range	-67°F– 230°F (-55°C– 110°C)
Type	WET-SHRINK Thick Wall Heat Shrink Adhesive
Min. Order UOM	PC
Min. Order Qty.	2
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.