



enabling technologies

[10 Gig Ethernet](#)
[Data Centers](#)
[Fiber System Deployment](#)
[Grounding System for Data Centers](#)
[Industrial Ethernet](#)
[Managing the Physical Layer](#)
[Network Security](#)
[Power Over Ethernet](#)

product information

[Products](#)
[Bill of Material](#)
[My Catalog](#)
[Part Search](#)
[Cross Reference](#)
[FAQ's](#)
[Download / Request Literature](#)
[Downloads](#)

resources to help you

[Evaluate Technologies](#)
[Design a Solution](#)
[How to Buy](#)
[Evaluate, Design & Install Products](#)
[Download Panduit Logo](#)
[White Papers](#)
[RoHS Compliance](#)

value added services

[Strategic Alliance Program](#)
[Consultants](#)
[Distributors](#)
[Installers](#)
[System Integrators](#)
[Warranties](#)

Product Information: Products

[USA](#) | [Heat Shrink & Abrasion Protection](#) | [Heat Shrink](#) | [General Purpose, Flexible Polyolefin for Dry Locations](#) |
Heat Shrink in 6 In. Pieces; Multi-Color, Single Diameter



evaluate

[FAQs](#)

design a solution

install & maintain

- Small package fits easily in tool box
- Shrink ratio of 2:1 insulates a wide range of diameters and irregular shapes
- Cross-linked, UV resistant material improves flame retardancy, chemical, and temperature resistance

~ Meets Mil Spec AMS-DTL-23053/5 Class 1 except clear which is manufactured from flammable polyolefin cross-linked material and meets AMS-DTL-23053/5 Class 2.

Part Number	HSTT100-YK1
Product Family	Heat Shrink in 6 In. Pieces; Multi-Color, Single Diameter
RoHS Compliant	Compliant
Part Description	Various Color 6" Pieces Thin Wall Polyolefin Heat Shrink
Material	Flame retardant polyolefin cross-linked except clear†
Color	1 pc. black 1 pc. of each color*
CSA Certified	Except Clear
Military Specification	AMS-DTL-23053/5 Class 1 (except clear†)
UL Recognized	E122770
Length (In.)	6.00
Length (mm)	152.4
Flammability Rating	Flame Retardant Except Clear
Max. Recovered I.D. (In.)	.500
Max. Recovered I.D. (mm)	12.7
Min. Expanded I.D. (In.)	1.00
Min. Expanded I.D. (mm)	25.4
Nominal Diameter / Size	1
Nominal Recovered Wall Thickness (In.)	.035
Nominal Recovered Wall Thickness (mm)	.9
Shrink Ratio	2:1
Std. Pkg. UOM	PK

Temperature Range -67°F to 275°F (-55°C to 135°C)

UOM PK

Std. Pkg. Qty. 1

Min. Order Qty 1

BOM Qty. (# of Pkgs.)

Add to My Catalog

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'My Catalog' features.

[legal information](#) | [privacy policy](#) | [site map](#)

Copyright © 1995-2005, PANDUIT CORP. All rights reserved.