

Search Results

- Evaluate  
- FAQ's  
How to Buy  
- Bill of Material  
- Favorite Products List  
- Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips  Within Results

 Text Search: 'HSTT38-48-Q2'


Your search criteria matched only one product, shown below

### HSTT38-48-Q2



- Shrink ratio of 2:1 insulates a wide range of diameters and irregular shapes
  - Cross-linked, UV resistant material improves flame retardancy, chemical, and temperature resistance
- For clear, add "C" to end of part number package suffix (Example HSTT05 -48-QC). Contact customer service for additional color information.

Meets Mil Spec AMSDTL-23053/5 Class 1 (Colors), Class 2 (Clear)

▪ Part Number	HSTT3848-Q2
▪ RoHS Compliancy Status	Compliant
▪ Part Description	Thin Wall Polyolefin Heat Shrink
▪ Material	Flame retardant polyolefin cross-linked except clear
▪ Color	Red
▪ CSA Certified	Yes
▪ Military Specification	AMS-DTL-23053/5 Class 1
▪ UL Recognized	E122770
▪ Length (ft.)	4
▪ Length (m)	1.2
▪ Flammability Rating	Flame Retardant
▪ Max. Recovered I.D. (In.)	.187
▪ Max. Recovered I.D. (mm)	4.8
▪ Min. Expanded I.D. (In.)	.375
▪ Min. Expanded I.D. (mm)	9.5
▪ Nominal Diameter / Size	.375
▪ Nominal Recovered Wall Thickness (In.)	.025
▪ Nominal Recovered Wall Thickness (mm)	.6
▪ Pricing Description	Heat Shrink Thin, .38"(9.5mm) Dia, White
▪ Shrink Ratio	2:1
▪ Temperature Range	-67°F to 275°F (-55°C to 135°C)
▪ Min. Order UOM	PC
▪ Min. Order Qty.	25
▪ BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
▪ Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.