

Current refinements (click  to remove)

Search Tips

Region **USA**  Product Family **HSTTA Heat Shrink**  Text Search: 'HSTTA38-48-Q'

Your search criteria matched only one product, shown below.



Dual Wall Polyolefin DAMPSHRINK™ Heat Shrink Tubing in 4 ft Pieces

- For damp locations
- Flexible tubing with an adhesive inner wall which seals and protects components from moisture and corrosion
- The 3:1 shrink ratio is a benefit when working with connector -to-cable transitions
- Material Type: Polyolefin CrossLinked with adhesive
- Shrink Ratio: 3:1
- Temperature Range:-67°F to 230°F (-55°C to 110°C)
- Flammability: Outer wall flame retardant
- Voltage Rating: 600V
- Mil Spec: AMSDTL-23053/4 Class 3

Part Number:	HSTTA38-48-Q
RoHS Compliancy Status:	Compliant
Part Description:	Dual Wall Adhesive Lined Thin Wall Heat Shrink
Material:	Polyolefin cross-linked with adhesive.
Color:	Black
Military Specification:	AMS-DTL-23053/4 Class 3
Length (ft.):	4
Flammability Rating:	Outer Wall Flame Retardant
Max. Recovered I.D. (In.):	.120
Max. Recovered I.D. (mm):	3.0
Min. Expanded I.D. (In.):	.375
Min. Expanded I.D. (mm):	9.5
Nominal Diameter (In.):	3/8
Nominal Diameter (mm):	9.5
Nominal Recovered Wall Thickness (In.):	.055
Nominal Recovered Wall Thickness (mm):	1.4
Shrink Ratio:	3:1
Temperature Range:	-67°F to 230°F(-55°C to 110°C)
Min. Order UOM:	PC
Min. Order Qty.:	25
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>

Add to My Catalog

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'My Catalog' features.