THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

PANDUIT INVENTORY NUMBERING SYSTEM

HSTTA 19 - 48 - Q

- HSTTA — ADHESIVE LINED THIN WALL HEAT SHRINK TUBING.
- 19 — EXPANDED INSIDE DIAMETER TUBING SIZE
- 48 — LENGTH: 48 = 48"(1219mm)
- Q — PACKAGE QUANTITY:

5	= 5	pcs.
Q	= 25	pcs.
TL	= 250	pcs.
T	= 200	pcs.
CQ	= 125	pcs.
LQ	= 75	pcs.
L	= 50	pcs.

PANDUIT PART NUMBER	Min. Exp. I.D In.(mm)	Max. Rec. I.D In.(mm)	NOMINAL REC WALL THICKNESS In.(mm)
HSTTA19-48-Q	.187 (4.8)	.062 (1.6)	.040±.010 (1.0±.0.3)
HSTTA25-48-Q	.250 (6.4)	.080 (2.0)	.040±.010 (1.0±.03)
HSTTA38-48-Q	.375 (9.5)	.120 (3.0)	.055±.012 (1.4±0.3)
HSTTA50-48-5	.500 (12.7)	.160 (4.1)	.070±.014 (1.8±0.4)
HSTTA75-48-5	.750 (19.0)	.250 (6.4)	.085±.017 (2.2±0.4)
HSTTA100-48-5	1.00 (25.4)	.320 (8.1)	.100±.020 (2.5±0.5)
HSTTA150-48-5	1.50 (38.1)	.510 (12.9)	.100±.020 (2.5±0.5)

NOTES:

1. SHRINK RATIO: 3:1
2. SHRINK RATIOS ARE APPROXIMATIONS; PLEASE REFER TO TABLE 1 FOR THE EXACT MIMIMUM EXPANDED AND MAXIMUM RECOVERED I.D 'S.
3. MATERIAL: POLYOLEFIN WITH ADHESIVE
4. COLOR: BLACK
5. "ALL WARRANTIES, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE EXCLUDED. (USER IS RESPONSIBLE TO DETERMINE SUITABILITY OF PRODUCT FOR INTENDED USE."

DIMENSIONS IN BRACKETS ARE METRIC [mm]

CAD FILENAME/LAYERS: G00239K0_PB_HSTTA_00

PANDUIT CORP. TINLEY PARK, ILLINOIS

FLEXIBLE ADHESIVE LINED THIN WALL HEAT SHRINK (HSTTA)

UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE:
(.X) ±0.05 [1.3] (.XXX) ±0.010 [0.25]
(.XX) ±0.02 [0.5] ANGLES ± 5°

UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE GIVEN IN INCHES. THIRD ANGLE PROJECTION.

DRAWN BY: LGRAVITT
MAT'L: SEE NOTES
SCALE: NONE
DATE: 5/14/03
CHK'D:
DRAWING NO.: GB0239K0
DWG SIZE: A

REV	DATE	BY	CHK	DESCRIPTION	ECN - R	CUST	SUP	
R	5/14/03	LGG	[illegible]	INITIAL RELEASE	GB0238K0	R	[illegible]	