

Search Results

- Evaluate
- FAQ's
- How to Buy
- Bill of Material
  - Favorite Products List
  - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips  Within Results

 Text Search: 'HSTTVA50-Y'

Your search criteria matched only one product, shown below

## HSTTVA50-Y



Dual Wall Polyolefin DAMP-SHRINK™ Heat Shrink Tubing in 6" Pieces

- For damp locations
- Flexible tubing with an adhesive inner wall which seals and protects components from moisture and corrosion
- For use when a flexible adhesive lined tubing is needed
- Material Type: Polyolefin Cross-Linked with adhesive
- Shrink ratio: 2:1
- Temperature range: -67°F to 230°F (-55°C to 110°C)
- Flammability: Outer wall flame retardant
- Voltage rating: 600 V
- Mil Spec: AMSDTL-23053/4 Class 2

▪ Part Number	HSTTVA50-Y
▪ RoHS Compliancy Status	Compliant
▪ Part Description	Dual Wall Adhesive Lined Thin Wall Heat Shrink (UL224 VW)
▪ Material	Polyolefin Cross-linked with adhesive
▪ Color	Black
▪ Military Specification	AMS-DTL-23053/4 Class 2
▪ Length (In.)	6.00
▪ Length (mm)	152.4
▪ Flammability Rating	Outer Wall Flame Retardant
▪ Max. Recovered I.D. (In.)	.250
▪ Max. Recovered I.D. (mm)	6.4
▪ Min. Expanded I.D. (In.)	.500
▪ Min. Expanded I.D. (mm)	12.7
▪ Nominal Diameter (In.)	.500
▪ Nominal Diameter (mm)	12.7
▪ Nominal Recovered Wall Thickness (In.)	.032
▪ Nominal Recovered Wall Thickness (mm)	0.8
▪ Pieces per Package	4
▪ Pricing Description	Heat Shrink Thin, Adhesive, .50"(12.7mm) Dia
▪ Shrink Ratio	2:1
▪ Temperature Range	-67°F to 230°F
▪ Min. Order UOM	PK
▪ Min. Order Qty.	1
▪ BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
▪ Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.