



Search Results

- Evaluate
 - FAQ's
 - Line Cards
 - PDF-NetKey Cabli ..
- Design a Solution
 - Part Drawings
 - PDF-NetKey Fiber ..
 - Specification Sheets
 - PDF-NetKey Fiber ..
- How to Buy
 - Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Product On-Line Catalog > Search Results >

Current refinements (click to remove) Search Tips [?](#)

Text Search: 'NKFLCSMAQ'

Your search criteria matched only one product, shown below

NKFLCSMAQ



- Meets TIA/EIA-568-B.3 requirements
- Insertion loss: .1dB typical (multimode), .2dB typical (singlemode)
- Return loss: >20dB (multimode), >40dB (singlemode)
- Non-optical disconnect maintains data transmission under tensile loads
- Each duplex plug includes housing, insert, two ferrule assemblies, two crimp sleeves, one boot for 3mm jacketed cable and two dust caps
- Fiber cable type: tight-buffered recommended
- Fiber cable size: 3.0mm jacketed cable or 1.6mm - 2.0mm jacketed cable (noted in part description)
- Field polish termination -- Panduit recommends anaerobic adhesive
- Use Field Polish Termination Kit (FIELDKIT)

▪ Part Number	NKFLCSMAQ
▪ RoHS Compliancy Status	Compliant
▪ Part Description	NetKey® LC 50/125µm OM3/OM4 Multimode Simplex Connector, Electric Ivory (EI) body, Aqua (AQ) boot.
▪ Product Type	NetKey® Network Components
▪ Boot Color	Aqua (AQ)
▪ Pricing Description	Netkey LC 50/125µm OM3 Multimode Simplex Connector (EI Body AQ Boot)
▪ Min. Order UOM	PC
▪ Min. Order Qty.	1
▪ BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
▪ Add to Favorite Product List	<input type="checkbox"/>

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.