THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

PANDUIT PART #		STUD SIZE	DIMENSIONS mm				
PREFIX	PK		A ±0,51	W ±0,25	C ±0,38	M ±0,51	H ±0,25
PM2-3F	-C -M	M3	16,00 (.63)	5,84 (.23)	5,59 (.22)	12,45 (.49)	3,30 (.13)
PM2-4F	-C -M	M4	17,53 (.69)	7,87 (.31)	6,35 (.25)	13,46 (.53)	4,57 (.18)
PM2-5F	-C -M	M5	18,03 (.71)	8,64 (.34)	6,86 (.27)	13,97 (.55)	5,33 (.21)
PM2-6F	-C -M	M6	22,35 (.88)	11,18 (.44)	8,89 (.35)	16,00 (.63)	6,60 (.26)



NOTES:

1. USED FOR:
   A. 1,5-2,5mm² (#16-14 AWG), SOLID OR STRANDED, COPPER WIRE
2. MATERIAL:
   A. STAMPING - 0,81mm (.03) THK COPPER, TIN PLATED
3. DIMENSIONS IN BRACKETS ARE IN INCHES
4. PACKAGE QTY:
   A. STD: C=100
   B. BULK: M=1000
5. WIRE STRIP LENGTH: $7,1^{+,8}_{-0}$ ($9/32^{+1/32}_{-0}$)
6. INSTALLATION TOOLS: REF. DWGS. A41522, A41523, A41524, A41525

A41428_01

REV	DATE	BY	CHK	DESCRIPTION	ECN #	CUST	PM
01	10/97	TM		CHANGED DECIMAL POINTS TO COMMAS			
00	11/91	BK	RS	RELEASED	00687	LA	KS

PANDUIT CORP. TINLEY PARK, ILLINOIS

NON-INSULATED METRIC FORKS
1,5-2,5mm² BARREL

DRAWN BY	CH'K'D	SCALE	DRAWING NO.
BDK		NONE	A41428