

Search Results

Evaluate

- FAQ's

Design a Solution

- Part Draw ings

- PDF-Locking Fork ..

How to Buy

- Bill of Material

- Favorite Products List

- Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips Within Results

 Text Search: 'PN18-8LF-M'

Your search criteria matched only one product, shown below

PN18-8LF-M



- Locks in place for secure connection
 - Fork design provides for fast and easy installation, without the need to remove fastener
 - Metal insulation grip sleeve crimps to wire insulation, providing protection to the crimp joint during high vibration applications
 - Internal barrel serrations assure good wire contact and maximum tensile strength
 - UL Flammability UL 94V-2/HB, maximum insulation temperature 221°F (105°C)
 - UL and CSA rated up to 600 V per UL 486
- ‡UL and CSA approved tooling/product combinations.

Part Number	PN18-8LF-M
RoHS Compliancy Status	Compliant
Part Description	Locking Fork Terminal, nylon insulated, 22 – 18 AWG, #8 stud size.
Product Type	Terminals
CSA Certified	Yes
UL Listed	Yes
Length (In.)	.89
Width (In.)	.29
Clearance	.25
Max. Ins.	.145
Panduit Color Code	Red
Pricing Description	Locking Fork Terminal, nylon insulated, 22 - 18 AWG, #8 stud size
Stud Size	#8
Tool	CT-100A‡, CT-600-A‡, CT-1550‡, CT-1551‡, CT-2500‡
Wire Range	22 – 18 AWG
Wire Range (mm²)	0.5 - 1.0
Min. Order UOM	PC
Min. Order Qty.	1000
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to Favorite Product List	<input type="checkbox"/>

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.