

Search Results

- Evaluate
- FAQ's
How to Buy
- Bill of Material
- Favorite Products List
- Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips  Within Results

 Text Search: 'PV18-14FB-3K'


Your search criteria matched only one product, shown below

PV18-14FB-3K



The PVC insulation forms an insulation crimp on the wire insulation. All polyvinylchloride 2 - piece insulated terminals are rated at 600 volts and designed for up to 105° C (221° F) operating temperature.

- Continuously molded design provides reliable, consistent performance through the applicator for a high quality termination every time
- Fork design provides for fast and easy installation, without the need to remove fastener
- Insulation support helps to prevent wire damage in bending applications
- Maximum insulation temperature 221°F (105°C)
- UL and CSA rated up 600 V per UL 486

▪ Part Number	PV18-14FB-3K
▪ RoHS Compliancy Status	Compliant
▪ Part Description	Fork Terminal, vinyl insulated, funnel entry, plastic insulation crimp, 22- 18 AWG wire range, 1/4" stud size.
▪ Product Type	Terminals- Reel Fed
▪ CSA Certified	Yes
▪ UL Listed	Yes
▪ Length (In.)	1.03
▪ Width (In.)	.44
▪ Barrel to Hole Length (In.)	.78
▪ CA-800 Series Crimp Die	CD-800-1
▪ CA9 Series Crimp Die	CD9-1A
▪ Clearance	.33
▪ Max. Ins.	.150
▪ Panduit Color Code	Red
▪ Pieces Per Reel	3000
▪ Pricing Description	Fork Terminal, vinyl insulated, 22- 18 AWG, 1/4" stud size, funnel entry
▪ Stock	.03
▪ Stud Size	1/4"
▪ Wire Range	22 – 18 AWG
▪ Wire Range (mm ²)	0.5 - 1.5
▪ Min. Order UOM	PC
▪ Min. Order Qty.	3000
▪ BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
▪ Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.