

Pan-Wrap™ Split Harness Wrap and Tool

More than just another harness wrap

**Engineered for flexibility and
maximum protection of wires
and cables**

Pan-Wrap™ Split Harness Wrap is an innovative addition to the Panduit abrasion protection line. It features slotted walls that provide flexibility and allow for easy breakouts along the length of the harness. Pan-Wrap™ Tools are available for quick and easy installation. The Pan-Wrap™ Product Line helps you to manage your physical infrastructure effectively.



Key Features

Benefits

Patented installation tool with 180° opening	Allows easy loading of maximum bundle diameters to speed installation, providing the lowest installed cost
Patented slot pattern	Provides improved flexibility and abrasion protection in any application Provides for easy wire or cable breakouts Maintains uniform bundle protection in dynamic applications
Large overlap	One size accommodates a wide range of bundle diameters, minimizing the part numbers to inventory
Packaged on a reel	Ensures easy handling and dispensing of product
Natural and flame retardant polyethylene material	Temperature range: -40°F to 122°F (-40°C to 50°C); meets a variety of application requirements; flame retardant option is manufactured from a material that is rated UL 94V-0 and has a temperature range of -4°F to 167°F (-20°C to 75°C)

Installation Instructions



Open Pan-Wrap™ Tool and insert bundle.



Close tool to contain bundle.



Slide Pan-Wrap™ Split Harness Wrap onto end of tool until approximately 3" of it covers the bundle.



Grasp end of Pan-Wrap™ Split Harness Wrap and bundle while pulling the tool along the bundle length.

Pan-Wrap™ Split Harness Wrap and Tool

Ordering Information

Part Number	Material**	Color	Length Per Reel		Max. Bundle Diameter		Min. Bundle Diameter‡		Nominal I.D.		Std. Pkg. Qty.*
			ft.	m	In.	mm	In.	mm	In.	mm	
PW38F-TL	Polyethylene	Natural	250	76.2	.43	10.9	.25	6.4	.38	9.7	1
NEW! PW38F-TL20	Polyethylene	Black	250	76.2	.43	10.9	.25	6.4	.38	9.7	1
PW50F-T20	Polyethylene	Black	200	61.0	.55	14.0	.43	10.9	.50	12.7	1
PW50F-T	Polyethylene	Natural	200	61.0	.55	14.0	.43	10.9	.50	12.7	1
PW75F-C20	Polyethylene	Black	100	30.5	.81	20.6	.55	14.0	.75	19.1	1
PW75F-C	Polyethylene	Natural	100	30.5	.81	20.6	.55	14.0	.75	19.1	1
PW100F-C	Polyethylene	Natural	100	30.5	1.13	28.7	.81	20.6	1.00	25.4	1
PW100F-C20	Polyethylene	Black	100	30.5	1.13	28.7	.81	20.6	1.00	25.4	1
PW150F-L	Polyethylene	Natural	50	15.2	1.63	41.4	1.13	28.7	1.50	38.1	1
PW150F-L20	Polyethylene	Black	50	15.2	1.63	41.4	1.13	28.7	1.50	38.1	1
NEW! PW38FR-TLY	Flame Retardant Polyethylene	Natural	250	76.2	.43	10.9	.25	6.4	.38	9.7	1
NEW! PW38FR-TL20Y	Flame Retardant Polyethylene	Black	250	76.2	.43	10.9	.25	6.4	.38	9.7	1
PW50FR-T	Flame Retardant Polyethylene	Natural	200	61.0	.55	14.0	.43	10.9	.50	12.7	1
PW50FR-T20	Flame Retardant Polyethylene	Black	200	61.0	.55	14.0	.43	10.9	.50	12.7	1
PW75FR-C	Flame Retardant Polyethylene	Natural	100	30.5	.81	20.6	.55	14.0	.75	19.1	1
PW75FR-C20	Flame Retardant Polyethylene	Black	100	30.5	.81	20.6	.55	14.0	.75	19.1	1
PW100FR-C	Flame Retardant Polyethylene	Natural	100	30.5	1.13	28.7	.81	20.6	1.00	25.4	1
PW100FR-C20	Flame Retardant Polyethylene	Black	100	30.5	1.13	28.7	.81	20.6	1.00	25.4	1
PW150FR-L	Flame Retardant Polyethylene	Natural	50	15.2	1.63	41.4	1.13	28.7	1.50	38.1	1
PW150FR-L20	Flame Retardant Polyethylene	Black	50	15.2	1.63	41.4	1.13	28.7	1.50	38.1	1

*Order number of reels required.

‡Diameter can be further reduced with the use of cable ties.

**Flame retardant products are manufactured from a material that is rated UL 94V-0.

Pan-Wrap™ Installation Tool



Part Number	Color	For Use With	Std. Pkg. Qty.*
NEW! PWT38	White	PW38F	1
PWT50	White	PW50F	1
PWT75	White	PW75F	1
PWT100	White	PW100F	1
PWT150	White	PW150F	1

*Order number of tools required.

WORLDWIDE SUBSIDIARIES AND SALES OFFICES

PANDUIT CANADA
Markham, Ontario
cs-cdn@panduit.com
Phone: 800.777.3300

PANDUIT EUROPE LTD.
London, UK
cs-emea@panduit.com
Phone: 44.20.8601.7200

PANDUIT SINGAPORE PTE. LTD.
Republic of Singapore
cs-ap@panduit.com
Phone: 65.6305.7575

PANDUIT JAPAN
Tokyo, Japan
cs-japan@panduit.com
Phone: 81.3.6863.6000

PANDUIT LATIN AMERICA
Jalisco, Mexico
cs-la@panduit.com
Phone: 52.33.3777.6000

PANDUIT AUSTRALIA PTY. LTD.
Victoria, Australia
cs-aus@panduit.com
Phone: 61.3.9794.9020

For a copy of Panduit product warranties, log on to www.panduit.com/warranty

For more information

Visit us at www.panduit.com

Contact Customer Service by email: cs@panduit.com
or by phone: 800-777-3300 and reference WACB17

PANDUIT®

©2009 Panduit Corp.
ALL RIGHTS RESERVED.
Product Bulletin Number **WW-WACB17**
10/2009