

Search Results

- Evaluate
 - FAQ's
- Design a Solution
 - Part Drawings
 - PDFNon-Shrink P ..
- How to Buy
 - Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips  Within Results

 Text Search: 'TV105-12M20Y'

Your search criteria matched only one product, shown below

TV105-12M20Y




Non-Shrink oil resistant flexible clear tubing on reel

- Provides insulation and protection for lead wires wire harness assemblies soldered joints and components in electrical and electronic equipment

- Material: Polyvinyl chloride (PVC)
- Voltage Rating: 300V and 600V
- All purpose flexible non -shrinkable
- Resistant to heat and moisture

Applicable Specifications:

- UL224 VW-1
- CSA C22.2 No. 198.1 (OFT)
- ASTM D-922 Grade CFR
- MIL-I-631 Type F, Form U, Grade C- Class 1 Category 1

Part Number	TV105-12M20Y
RoHS Compliance Status	Compliant
Note	TV105-12M20Y replaces TV105-12D20Y
Part Description	PVC Non-Shrink Tubing, 105°C rated
Material	Polyvinyl Chloride
Color	Black
CSA Certified	Yes
CSA Specification	CSA C22.2 No. 198.1 (OFT)
UL Recognized	E122770
UL Recognized Specification	UL224 VW-1
Flammability Rating	UL224 VW-1
Length Per Reel (ft.)	1000
Length Per Reel (m)	304.8
Max. Inside Diameter (In.)	.089
Max. Inside Diameter (mm)	2.26
Max. Voltage Rating	300 V
Min. Inside Diameter (mm)	2.06
Minimum Inside Diameter (In.)	.081
Nominal Size	12 AWG
Pricing Description	Vinyl Tubing, 12 AWG (2.26mm), 300V, Black
Temperature Range	-4°F to 221°F (-20°C to 105°C)
Wall Thickness (In.)	.016
Wall Thickness (mm)	.41
Min. Order UOM	RL
Min. Order Qty.	1
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.