

Search Results

- Evaluate
  - FAQ's
- Design a Solution
  - Part Drawings
  - PDFNon-Shrink P ..
- How to Buy
  - Bill of Material
  - Favorite Products List
  - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips  Within Results

 Text Search: 'TV105-.75TLY'

Your search criteria matched only one product, shown below

**TV105-.75TLY**




Non-Shrink oil resistant flexible clear tubing on reel

- Provides insulation and protection for lead wires wire harness assemblies soldered joints and components in electrical and electronic equipment
- Material: Polyvinyl chloride (PVC)
- Voltage Rating: 300V and 600V
- All purpose flexible non -shrinkable
- Resistant to heat and moisture

Applicable Specifications:

- UL224 VW-1
- CSA C22.2 No. 198.1 (OFT)
- ASTM D-922 Grade CFR
- MIL-I-631 Type F, Form U, Grade C- Class 1 Category 1

Part Number	TV105-.75TLY
RoHS Compliance Status	Compliant
Note	TV105-.75TLY replaces TV105-.75CY
Part Description	PVC Non-Shrink Tubing, 105°C rated
Material	Polyvinyl Chloride
Color	Clear
CSA Certified	Yes
CSA Specification	CSA C22.2 No. 198.1 (OFT)
UL Recognized	E122770
UL Recognized Specification	UL224 VW-1
Flammability Rating	UL224 VW-1
Length Per Reel (ft.)	250
Length Per Reel (m)	76.2
Max. Inside Diameter (In.)	.786
Max. Inside Diameter (mm)	19.96
Max. Voltage Rating	600 V
Min. Inside Diameter (mm)	19.05
Minimum Inside Diameter (In.)	.750
Nominal Size	3/4
Pricing Description	Vinyl Tubing, .75" (19.1mm), 600V, Clear
Temperature Range	-4°F to 221°F (-20°C to 105°C)
Wall Thickness (In.)	.035
Wall Thickness (mm)	.89
Min. Order UOM	RL
Min. Order Qty.	1
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.