

## Fiber optic coupling - FOC-I-D1PGY-S/MPBGC - 1041840

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Fiber optic coupling, degree of protection: IP20, connection method: Coupling, cable outlet: straight

### Your advantages

- Assembly without special tools
- Flexible use, thanks to DIN rail and direct mounting
- Space-saving design
- With dust protection caps



### Key Commercial Data

Packing unit	1 pc
GTIN	 4 055626 598680
GTIN	4055626598680

### Technical data

#### Mechanical characteristics

Connection method	Coupling
Number of slots	1
Cable outlet	straight
No. of cable outlets	2
Weight	7.9 g

#### Ambient conditions

Ambient temperature (operation)	-10 °C ... 70 °C
Degree of protection	IP20

#### Material data

Mounting type	Snap in
---------------	---------

### Standards and Regulations

# Fiber optic coupling - FOC-I-D1PGY-S/MPBGC - 1041840

## Technical data

### Standards and Regulations

Flammability rating according to UL 94	V0
--	----

## Classifications

### eCl@ss

eCl@ss 10.0.1	27061803
eCl@ss 4.0	24010400
eCl@ss 4.1	24010400
eCl@ss 5.0	19030300
eCl@ss 5.1	19030300
eCl@ss 6.0	27061800
eCl@ss 7.0	27061803
eCl@ss 9.0	27061803

### ETIM

ETIM 6.0	EC000034
ETIM 7.0	EC000034

## Accessories

### Accessories

#### Patch panel

DIN rail adapter - NBC-PP-G1PGY - 1041740



DIN rail adapter, type: Headers with shielding, degree of protection: IP20, material: PC-GF10, without assembled modules

Marshalling panel - CUC-PP-FR19:1U-I-EMPTY:24 - 1422978

Patch bay, 19" mounting, IP20, with 24 slots selectively for RJ45 cable connection modules, RJ45 coupling modules, LC duplex, SC simplex and MPO, medium gray



## Fiber optic coupling - FOC-I-D1PGY-S/MPBGC - 1041840

### Accessories

Marshalling panel - CUC-PP-FR19:1U-I-EMPTY:24 BK - 1422979



---

### Necessary add-on products

DIN rail adapter - NBC-PP-G1PGY - 1041740



DIN rail adapter, type: Headers with shielding, degree of protection: IP20, material: PC-GF10, without assembled modules

---

Phoenix Contact 2020 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>