

Panel mounting frames - VS-V1-F-RJ45-MNNA-1-C-S-JI-S - 1419185

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



RJ45 mounting frame, IP67, for bayonet interlocking, metal, with contact insert for cable connection, for round mounting cutout, with seal, without mounting screws

Why buy this product

- Round panel cutout
- IP65/67
- Bayonet locking



Key Commercial Data

Packing unit	1 STK
GTIN	
GTIN	4046356540384

Technical data

Mechanical characteristics

Number of positions	8
Number of slots	1
Insertion/withdrawal cycles	750
Connection cross section AWG	26 ... 22 (flexible)
Wire diameter	0.4 mm ... 0.64 mm
Wire diameter including insulation	1.6 mm
Degree of protection	IP67
Type	RJ45, IP67, version 1
Type of note	Order information:
Note	Without mounting screws

Ambient conditions

Ambient temperature (operation)	-40 °C ... 70 °C
---------------------------------	------------------

Panel mounting frames - VS-V1-F-RJ45-MNNA-1-C-S-JI-S - 1419185

Technical data

Material data

Flammability rating according to UL 94	V0
Housing material	Zinc die-cast
Seal material	NBR

Electrical characteristics


Number of positions	8
Transmission characteristics (category)	CAT5 (IEC 11801:2002)
GRP transmission properties	CAT5 (IEC 11801:2002) CAT5 (IEC 11801:2002)
Transmission speed	1 Gbps
Rated voltage (III/3)	72 V (DC)

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Drawings

Dimensional drawing



Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC		B.01742
-----	--	---------

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>