

Patch panels - FOC-FR19:1U-2OS12-LCD12-OM1 - 1419973

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Your advantages

- ✓ Fast and reliable cabling, thanks to clear connections on the front
- ✓ Plug & Play
- ✓ Compact design with MT ferrule



Key Commercial Data

Packing unit	1 pc
GTIN	 4 055626 198903
GTIN	4055626198903

Technical data

Mechanical characteristics

Number of slots	12
No. of cable outlets	0
Locking type	Push Pull
Weight	1770 g

Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C (IEC 61300-2-22)
Degree of protection	IP20
	IP20

Material data

Housing material	Aluminum alloy
Housing surface material	Powder-coated, gray
Width	482.6 mm

Patch panels - FOC-FR19:1U-2OS12-LCD12-OM1 - 1419973

Technical data

Material data

Height	132 mm
Depth	220 mm
Mounting type	Screw mounting

Standards and Regulations

Halogen-free	complying with IEC 60754-1/2
Flammability rating according to UL 94	V0

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50 years
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss

eCl@ss 10.0.1	27440219
eCl@ss 8.0	27440102
eCl@ss 9.0	27440219

Accessories

Additional products

Connecting cable - FOC-OP12-OP12-GL02/10 - 1415353



Double-end preassembled cable, type: circular connector, degree of protection: IP68, number of positions: 12

Phoenix Contact 2020 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>