

Printed-circuit board connector - CCVA 2,5/10-G P20 THR - 1837103


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

PCB headers, nominal current: 12 A, rated voltage (III/2): 320 V, number of positions: 10, pitch: 5 mm, color: black, contact surface: Tin, mounting: THR soldering, User information and design recommendations for through hole reflow technology can be found under "Downloads"




Your advantages

- ✓ Designed for integration into the SMT soldering process
- ✓ Maximum flexibility when it comes to device design – one header for connectors with different connection technologies
- ✓ Closed contour for optimum stability of the plug-in connection



Key Commercial Data

| | |
|--------------|--|
| Packing unit | 50 pc |
| GTIN |  4 055626 021577 |
| GTIN | 4055626021577 |

Technical data

Dimensions

| | |
|--------------------------|----------|
| Length [l] | 8.57 mm |
| Width | 52.8 mm |
| Pitch | 5 mm |
| Dimension a | 45 mm |
| Width [w] | 52.8 mm |
| Height [h] | 14 mm |
| Height | 12 mm |
| Length of the solder pin | 2 mm |
| Pin dimensions | 1 x 1 mm |
| Length | 8.57 mm |

General

| | |
|---------------------------|---------------|
| Range of articles | CCVA 2,5/..-G |
| Insulating material group | IIIa |

Printed-circuit board connector - CCVA 2,5/10-G P20 THR - 1837103

Technical data

General

| | |
|--|---------------------|
| Rated surge voltage (III/3) | 4 kV |
| Rated surge voltage (III/2) | 4 kV |
| Rated surge voltage (II/2) | 4 kV |
| Rated voltage (III/3) | 250 V |
| Rated voltage (III/2) | 320 V |
| Rated voltage (II/2) | 400 V |
| Connection in acc. with standard | EN-VDE |
| Nominal current I _N | 12 A |
| Maximum load current | 12 A (per position) |
| Insulating material | LCP |
| Flammability rating according to UL 94 | V0 |
| Color | black |
| Number of positions | 10 |

Packaging information

| | |
|----------------------------|---------------------|
| Type of packaging | packed in cardboard |
| Pieces per package | 50 |
| Denomination packing units | Pcs. |

Standards and Regulations

| | |
|--|--------|
| Connection in acc. with standard | EN-VDE |
| Flammability rating according to UL 94 | V0 |

Environmental Product Compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

Approvals

Approvals

Approvals


cULus Recognized

Ex Approvals

Approval details

Printed-circuit board connector - CCVA 2,5/10-G P20 THR - 1837103

Approvals

| | | |
|--------------------|---|---|
| cULus Recognized |  | http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm E60425-19931011 |
| | D | B |
| Nominal voltage UN | 300 V | 300 V |
| Nominal current IN | 10 A | 16 A |

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>