



Kit, for CompactPCI, for backplane mounting, without rear I/O, shielded

Catalog Number:24563-152

[Back To Product](#)

- Shielding typically 1GHz = 40dB, 2GHz = 30dB, assuming that the front is closed with shielded front panels
- Subrack with side panel type F ("flexible") for CompactPCI plug-in units with high insertion and withdrawal forces
- Horizontal rail rear for backplane mounting with insulation strip
- Installed load up to 11 kg
- Shielding typically 40 dB at 1 GHz, 30 dB at 2 GHz, assuming that the front is covered with shielded front panels
- For CompactPCI plug-in units to IEEE 1101.10
- europacPRO "flexible" version
- With and without rear I/O



Products per Package:

1.0

Products per Package:

1.0

[Change Item](#) >

CHANGING AN ITEM WILL UPDATE THE CATALOG NUMBER. THIS CAN AFFECT THE LIST PRICE AND SPECIFICATION OF THE ITEM.

Quantity

1

[Add Item to Project List](#) +

Description Downloads **Items** Accessories

Kit, for CompactPCI, for backplane mounting, without rear I/O, shielded

Catalog Number 24563-152

Width HP 84.0

Depth D1 mm 175

Description shielded (IEEE)

EXPLORE

- About Us
- Services & Capabilities
- News and Events
- Strategic Partnerships
- Investor Relations

CONTACT

- Customer Service
- Find a Sales Office or Distributor
- Global Locations
- Product Compliance & Certifications
- Partner Login

DOWNLOAD

- Literature
- White Papers & Case Studies
- Videos & Mobile Apps
- Product Configurators
- Warranties