

Sealing for Appliance Inlets



6100 with sealing to appliance



Description


Protects from ingressing fluids and dust into the appliance - 1 Function:

Weblinks

[pdf-datasheet](#), [html-datasheet](#), [General Product Information](#), [Approvals](#), [CE declaration of conformity](#), [RoHS](#), [CHINA-RoHS](#), [Mating Connectors](#), [e-Shop](#), [SCHURTER-Stock-Check](#), [Distributor-Stock-Check](#), [CAD-Drawings](#), [Accessories](#), [Mounting instruction](#), [Detailed request for product](#)


Mounting instructions

1) Mounted from front side



- Panel thickness max. 3 mm
- Tightening torque max 0.1 Nm
- 1 Chassis
- 2 Appliance inlet
- 3 Flat gasket (included in 0098.0103)
- 4 Srew with sealing (included in 0098.0103)
- 5 Lock washer (not part of kit)
- 6 Nut 0.8d (not part of kit)

1) Mounted from rear side



- Panel thickness max. 3 mm
- Tightening torque max 0.1 Nm

Variants

Suitable for	Degree of Protection	Mounting side	Mounting instruction	Mounting option	Order Number
6100-3, 6120-3	IP 54	Front-/Rear-Side	1)	Screws included	0098.0103