Audio Connector, Socket, 2.5 mm, 2-pole, solder terminal, shielded







Description

- Solder terminal: Screw-on mounting, from rear-side
- Audio entrances and exits
- Data and Signal transfer
- Audio Plug: 2-pole, shielded, straight

Weblinks


pdf-datasheet, html-datasheet, General Product Information, RoHS, CHINA-RoHS, REACH, Mating Connectors, e-Shop, SCHURTER-Stock-Check, Distributor-Stock-Check

Technical Data


Diameter	2.5 mm		
Number of Poles	2-pole		
Ratings DC	0.5 A / 30 VDC		
Ratings AC	0.5 A / 30 VAC		
Dielectric Strength	500 VDC		
Insulation Resistance	> 100 MΩ @ 500 VDC		

Allowable Operation Temp.	-20°C to 70°C
Terminal	solder terminal silver plated
Mounting	Screw-on mounting wall thickness max. 1.5 mm
Housing	screened
Style	straight
Lifetime	5000 Insertions

Dimensions



Diagrams



All Variants

Product group	Diameter [mm]	Number of Poles	Terminal	Order Number
Audio Plug/Sockets	2.5	2-pole	solder terminal	4831.2200

Availability for all products can be searched real-time:http://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER

Packaging unit

500 Pcs

Mating Inlets/Plugs

Category / Description

Audio Plug/Sockets Overview complete



4831, solder terminal, screened, 2-pole, Audio Plug/Sockets, 2.5 mm	4831.1200
4831, solder terminal, insulated, 2-pole, Audio Plug/Sockets, 2.5 mm	4831.1210
4831, solder terminal, insulated, 2-pole, Audio Plug/Sockets, 2.5 mm	4831.1220

Audio Plug/Sockets further types to 4831 Audio-Stecker, D=2,5mm