

Audio Connector, Plug, 3.5 mm, 2-pole, solder terminal, shielded



Description

- Solder terminal: for cable mounting
- Audio entrances and exits
- Data and Signal transfer
- Audio Plug: 2-pole, shielded, straight

References

Alternative: Housing insulated [4832.1211](#); [4832.1220](#)


Weblinks

[pdf-datasheet](#), [html-datasheet](#), [General Product Information](#), [RoHS](#), [CHINA-RoHS](#), [REACH](#), [Mating Connectors](#), [e-Shop](#), [SCHURTER-Stock-Check](#), [Distributor-Stock-Check](#)

Technical Data

Diameter	3.5 mm	Allowable Operation Temp.	-20 °C to 70 °C
Number of Poles	2-pole	Terminal	solder terminal nickel-plated
Ratings DC	0.5 A / 30VDC	Housing	screened
Ratings AC	0.5 A / 30VAC	Style	straight
Dielectric Strength	500VDC	Lifetime	5000 Insertions
Insulation Resistance	> 100 MΩ @ 500VDC		

Dimensions



Cable diameter max. 4.0 mm

All Variants

Product group	Diameter [mm]	Number of Poles	Terminal	Order Number
Audio Plug/Sockets	3.5	2-pole	solder terminal	4832.1200

Availability for all products can be searched real-time: <http://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER>

Packaging unit 100 Pcs

Mating Outlets/Connectors

Category / Description


[Audio Plug/Sockets Overview complete](#)

4832, solder terminal, screened, 2-pole, Audio Plug/Sockets, 3.5 mm	4832.2211
4832, PCB terminals, screened, 2-pole, Audio Plug/Sockets, 3.5 mm	4832.2220
4832, PCB terminals, insulated, 2-pole, Audio Plug/Sockets, 3.5 mm	4832.2230
4832, solder terminal, insulated, 2-pole, Audio Plug/Sockets, 3.5 mm	4832.3200

[Audio Plug/Sockets further types to 4832 Audio-Stecker, D=3,5mm](#)