



## Cordsets



**Our Products**

New Products

- [Fuses](#)
- [Power Entry Modules](#)
- [Circuit Breakers](#)
- [Switches & Keypads](#)
- [RoHS](#)

Fuses

- [RoHS](#)
- [Non Resettable](#)
- [Resettable](#)
- [Surge Tolerant](#)

Fuseholders

- [RoHS](#)

Switches and Pushbuttons

- [vandal-proof - Metal Line](#)
- [Frontpanel Line](#)
- [Printmount Line](#)
- [Sensor Line](#)

Keyboard Systems

- [vandal-proof - Metal Line](#)
- [Touch Screen - Keypad Line](#)

Power Entry Modules

- [RoHS](#)
- [with Line Filter](#)
- [without Line Filter](#)

Block Filters

Inlets/ Outlets

- [Single Units](#)
- [Multiple Units](#)

Cord Connectors and Cordsets

Circuit Breakers for Equipment

- [thermal T-Line](#)
- [thermal TA45](#)
- [thermal-magnetic TM12](#)
- [thermal-magnetic AS168X](#)

Other Products

- [Data & Signal Connectors](#)
- [Indicator Lights](#)

CONNECTOR	IEC / EN 60320-1 / C13, protection class I, pin temperatur 70°C (cold condition)			
<b>TYPE</b>	<b>6010</b>			
<b>PLUG</b>	North America	Japan	Continental Europe	United Kingdom
<b>STANDARD</b>	NEMA 5-15	JIS 8303	CEE 7 / VII	BS 1363A (fuse fitted)
<b>CORD TYPE</b>	SJT	HVCTF3G0.75	H05VV-F3G1.0	H05VV-F3G0.75 (3A + 5A) H05VV-F3G1.0 (13A)
<b>CONDUCTOR</b>	3 x 18 AWG	3 x 0.75 mm <sup>2</sup>	3 x 1.00mm <sup>2</sup>	3 x 0.75 mm <sup>2</sup> (3A + 5A) 3 x 1.00 mm <sup>2</sup> (13A)
<b>RATED</b>	10 A / 125 V	7 A / 125 V	10 A / 250 V	10 A / 250 V
<b>COLOUR</b>	black	black	black	black
<b>LENGTH</b>	2.5 meters	2.0 meters	2.5 meters	2.0 meters (3A+5A) 2.5 meters (13A)
Cordsets supplied by SCHURTER carry the country specific approvals				
<b>ORDER NUMBER</b>	6009.1315	6047.6414	6003.0215	6045.0114 (3A) 6043.0114 (5A) 6044.0215 (13A)