CN Power Cord with IEC Appliance Connector C19, V-Lock, straight















Description

- Power Cord,
- Protection class I, Pin temperature 70 °C,
- with V-Lock interlocking system

Technical Data

Ratings IEC	16A / 250 VAC; 50/60 Hz
Dielectric Strength	> 2 kVDC between L-N
	> 2 kVAC between L/N-PE
	(1 min/50 Hz)
Allowable Operation Temp.	-25 °C to 70 °C
Degree of Protection	from front side IP 20 acc. to IEC 60529
Protection Class	Suitable for appliances with protection
	class I acc. to IEC 61140
Terminal	moulded
Material: Housing	PVC, black

Connector	C19 acc. to IEC 60320-1
	(for cold conditions) pin-temperature 70
	°C, 16A, Protection Class I

All Variants

All Variants											
Connector cable			'		Plug	Plug			Order Number		
Туре	V-Lock	Cord Type	Conductor cross section	Length [m]	Color	Туре	Country	Standard	Style	Index	
C19	•	RVV 300/500 3x1 5	3 x 1.5 mm ²	2.0	black	China	CN	GB 2099	straight	-	6051.2052

Most Popular.

 $\label{thm:comsum} \mbox{Availability for all products can be searched real-time:http://www.schurter.com/Stock-Check/Stock-Check-SCHURTER} \mbox{\cite{thm:comsumers}} \$

40 Pcs Packaging unit

Mating Inlets/Plugs shuttered

Category / Description



Appliance Inlet Overview complete

IEC Appliance Inlet C20 or C24, Split panel or screw-on mounting, PCB Terminal	GSP4
IEC Appliance Inlet C20, Screw-on Mounting, Rear Side, PCB Terminal	1601
IEC Appliance Inlet C20, Screw-on Mounting, Front Side, Solder or Quick-connect Terminal	4798
IEC Appliance Inlet C20, Snap-in Mounting, Front Side, Solder or Quick-connect Terminal	4793
IEC Appliance Inlet C20, Snap-in Mounting, Front Side, Solder or Quick Connect Terminal	1624
Appliance Inlet further types to 6051.2052	



Power Entry Module Overview complete

IEC Appliance Inlet C20 with Line Switch, 2-pole	EC11
000000	6136
IEC Appliance Inlet C20 with Circuit Breaker TA45	EF11

Power Entry Module further types to 6051.2052



Power Entry Module with line filter Overview complete

EC12, 20 A, prewired, Standard and Medical Version, Quick connect terminals 6.3 x 0.8 mm, Capacitor: X2, Screw, Mounting Front-Side, Power Entry Modules with Filter	EC12
IEC Appliance Inlet C20 with Filter, Circuit Breaker TA45 (recessed)	EF12
IEC Appliance Inlet C20 with Filter, ECO design, front or rear side Mounting	5130
C20F, 20 A, prewired, Standard and Medical Version, Solder, quick connect or wires (stranded), Capacitor: X2, Screw, Mounting Front-/Rear-Side, Power Entry Modules with Filter	C20F
Power Entry Module with line filter further types to 6051.2052	