

Straight DC Power Jacks



Straight versions of our DC power jacks. These versions have threaded bushings to allow use of both standard and locking power plugs. The L versions of the power jacks have a longer bushing (0.319") to accommodate thicker panel mount applications. Available in pin diameters of 0.050", 0.080", and 0.100".

[enlarge](#)

Products

Specifications

Downloads

[Need more info? Contact Switchcraft customer service](#)

Product	Description	Typical Mating	Layout	Drawings	Distributor Inventory
712A	DC Power Jack, 0.100" (2.5mm) pin, solder lugs termination	760			check stock
722A	DC Power Jack, 0.080" (2.0mm) pin, solder lugs termination	S760			check stock
732A	DC Power Jack, 0.050" (1.3mm) pin, solder lugs termination	860			check stock
L712A	DC Power Jack, 0.100" (2.5mm) pin, solder lugs termination, long bushing	761K			check stock
L722A	DC Power Jack, 0.080" (2.0mm) pin, solder lugs termination, long bushing	S761K			check stock
PC712A	DC Power Jack, 0.100" (2.5mm) pin, straight PC terminals	760			check stock
PC722A	DC Power Jack, 0.080" (2.0mm) pin, straight PC terminals	S760			check stock
PCL712A	DC Power Jack, 0.100" (2.5mm) pin, straight PC terminals, long bushing	761K			check stock
PCL722A	DC Power Jack, 0.080" (2.0mm) pin, straight PC terminals, long bushing	S761K			check stock
2C1072	DC Power Jack Cover, for use with 712A and 722A				check stock
P2439	Nickel Plated Brass Hex Nut				check stock
P2441	Nickel Plated Steel Flat Washer				check stock
P2442	Phenolic Flat Washer				check stock

denotes a special order