


C3225X5R0J476M250AA (TDK item description : C3225X5R0J476MT****)

Applications  Commercial Grade

Feature  General (Up to 50V)

Series C3225 [EIA CC1210]



Size	
Length(L)	3.20mm +/-0.40mm
Width(W)	2.50mm +/-0.30mm
Thickness(T)	2.50mm +/-0.30mm
Terminal Width(B)	0.20mm Min.
Terminal Spacing(G)	
Recommended Land Pattern(PA)	2.00 to 2.40mm
Recommended Land Pattern(PB)	1.00 to 1.20mm
Recommended Land Pattern(PC)	1.90 to 2.50mm
Recommended Slit Pattern(SD)	


Electrical Characteristics	
Capacitance	47uF +/-20%
Rated Voltage	6.3Vdc
Temperature Characteristic	X5R(+/-15%)
Dissipation Factor	7.5% Max.
Insulation Resistance	2MΩ Min.

Other	
Soldering Method	Reflow
AEC Q200	No
Packing	Blister (Plastic)Taping [180mm Reel]
Package Quantity	1000Pcs Min.


•This PDF document was created based on the data listed on the TDK Corporation website.
 •All specifications are subject to change without notice.

C3225X5R0J476M250AA


Characteristic Graphs (This is reference data, and does not guarantee the product's characteristics.)




C3225X5R0J476M250AA




C3225X5R0J476M250AA




C3225X5R0J476M250AA



C3225X5R0J476M250AA



C3225X5R0J476M250AA(DC Bias = 0V) C3225X5R0J476M250AA(DC Bias = 3.15V)



C3225X5R0J476M250AA(100kHz) C3225X5R0J476M250AA(500kHz)
C3225X5R0J476M250AA(1MHz)

•This PDF document was created based on the data listed on the TDK Corporation website.
•All specifications are subject to change without notice.