

## 1060464-1 Product Details

[Live Product Chat](#)



### 1060464-1

TE Part Number: 1060464-1

[Active](#)

[Add to Part List](#)

### SMB RF Connectors

[Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

#### Product Highlights:

- Connector
- Jack
- Standard
- Terminate To Printed Circuit Board
- Coupler Style = Quick Connect/Disconnect

[View all Features](#) | [Find Similar Products](#)

### Quick Links

- ▶ [Check Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)
- ▶ [Request Samples](#)

**NEW!**

### Documentation & Additional Information

#### Product Drawings:

- [SMB RIGHT ANGLE PRINTED CIRCUIT BOARD JACK RECEPTACL...](#) (PDF, English)

#### Catalog Pages/Data Sheets:

- None Available

#### Product Specifications:

- None Available

#### Application Specifications:

- None Available

#### Instruction Sheets:

- None Available

#### CAD Files:

- None Available

#### Additional Information:

- [Product Line Information](#)

#### Related Products:

- [Tooling](#)

[List all Documents](#)

### Product Features (Please use the Product Drawing for all design activity)

#### Product Type Features:

- [Product Type](#) = Connector
- [Gender](#) = Jack
- Connector Series = Standard
- [Body Style](#) = Right Angle
- [Grade](#) = Commercial
- [PCB Mount Angle](#) = Right Angle
- [Board Standoff](#) = With
- PCB Mount Style = Thru Hole
- Profile = Standard
- Dielectric Material = PTFE Fluorocarbon

#### Mechanical Attachment:

- [Panel Attachment](#) = Without

#### Electrical Characteristics:

- [Connector Impedance \(Ω\)](#) = 50
- Environmental Seal = Without

#### Body Related Features:

- Coupler Style = Quick Connect/Disconnect
- [Pin Protection](#) = Without
- Solder Lug = Without
- [Body Plating](#) = Gold

#### Contact Related Features:

- [Center Contact Plating](#) = Gold
- Contacts = With

#### Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C, Reflow solder capable to 245°C, Reflow solder capable to 260°C, Pin-in-Paste capable to 245°C, Pin-in-Paste capable to 260°C
- RoHS/ELV Compliance History = Always was RoHS compliant

#### Conditions for Usage:

- [Terminate To](#) = Printed Circuit Board

#### Other:

- Brand = AMP

[Provide Website Feedback](#) | [Need Help?](#)