

## 1116504-2 Product Details


### Have a Question?

Chat with a Product Information Specialist



**1116504-2**

TE Internal Number: 1116504-2

 **Active**

 [View 3D PDF](#)

### PCB Mounted Jacks - Single Port, Multi-port and Stacked

 [Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

#### Product Highlights:

- Connector
- Preloaded
- Single Port Configuration
- 1 x 1 Jack Configuration
- Jack Type = RJ45

[View all Features](#)

### Quick Links

- ▶ [Check Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

 [Add to My Part List](#)  [Request Sample](#)  [Find Similar Products](#)  [Buy Product](#)

### Documentation & Additional Information

#### Product Drawings:

- [MODULAR JACK ASSEMBLY, 8 POSITION, 10mm](#) (PDF, English)

#### Catalog Pages/Data Sheets:

- None Available

#### Product Specifications:

- [High Performance Modular Plugs & Jacks, PCB Mounted](#) (PDF, English)

#### Application Specifications:

- [Modular Jacks](#) (PDF, English)

#### Instruction Sheets:

- None Available

#### CAD Files: ([CAD Format & Compression Information](#))

- [2D Drawing](#) (DXF, Version J)
- [3D Model](#) (IGES, Version J)
- [3D Model](#) (STEP, Version J)

[List all Documents](#)

#### Additional Information:

- [Product Line Information](#)

#### Related Products:

- [Tooling](#)

### Product Features (Please use the Product Drawing for all design activity)

#### Product Type Features:

- Product Type = Connector
- [Jack Type](#) = RJ45
- [PCB Mount Angle](#) = Side Entry (Right Angle)
- [PCB Mount Style](#) = Through Hole
- [PCB Termination Type](#) = Solder
- [Performance Category](#) = Cat 5
- Number of Contacts Loaded = 8
- Grounding Options = Without
- [Panel Stops](#) = Without
- [Keved](#) = No
- [Profile](#) = Low
- [Color](#) = Black
- Latch Style = Standard
- Comment = Recommended applications: Fast Ethernet, 10Base-T Ethernet, and 10/100 Base-T Ethernet (Cat 5 on two pair 1/2, 3/6).

#### Mechanical Attachment:

- [Jack Configuration](#) = 1 x 1
- [Panel Attachment](#) = With
- Flanged = No

#### Electrical Characteristics:

- [Shielded](#) = No

#### Termination Related Features:

- [Height \(mm \[in\]\)](#) = 9.30 [0.366]
- [Solder Tail Contact Plating](#) = Tin over Nickel

#### Body Related Features:

- Port Configuration = Single
- [Number of Positions](#) = 8
- [Inverted Jack Face](#) = No
- [LED](#) = Without
- [PCB Tail Length \(mm \[in\]\)](#) = 3.48 [0.137]

#### Contact Related Features:

- Preloaded = Yes
- [Contact Plating, Mating Area, Material](#) = Gold (50)
- Contact Base Material = Phosphor Bronze

#### Housing Related Features:

- Housing Material = High Temperature Nylon
- UL Flammability Rating = UL 94V-0

#### Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

#### Conditions for Usage:

- [PCB Thickness, Recommended \(mm \[in\]\)](#) = 1.57 [0.062]

#### Packaging Related Features:

- Packaging Method = Tray

#### Other:

- Brand = AMP

 [BOOKMARK](#)   

### Corporate Information

[Who We Are](#)  
[Investors](#)  
[News Room](#)  
[Supplier Portal](#)  
[Careers](#)


### Quick Links

[Check Distributor Inventory](#)  
[Cross Reference](#)  
[Find Documents & Drawings](#)  
[Product Compliance Support Center](#)  
[Site Map](#)

### Customer Support

[Email or Chat with Us](#)  
[Find a Phone Number](#)  
[Search Knowledge Base](#)  
[Manage Your Account](#)

### Sign up for our eNewsletter

Enter your email address 

Follow us on: 