


Product Details for 1 -1337477 -0



1 -1337477 -0

[Active](#)

SMB RF Connectors

[RoHS Compliant \(Statement of Compliance\)](#)

Product Highlights:

- ? Connector
- ? Jack
- ? Standard
- ? Terminate To Coaxial Cable
- ? Coupler Style = Snap -On

[View all Features](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

Documentation & Additional Information

Product Drawings:

- ? [SMB STRAIGHT JACK CRIMP 50 OHM RG174A/U, 188A/U, 316...](#)
(PDF, English)

Catalog Pages/Data Sheets:

- ? None Available

Product Specifications:

- ? None Available

Application Specifications:

- ? None Available

Instruction Sheets:

- ? None Available

CAD Files:

- ? None Available

Additional Information:

- ? [Product Line Information](#)

Related Products:

- ? [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- ? [Product Type](#) = Connector
- ? [Gender](#) = Jack
- ? Connector Series = Standard
- ? [Body Style](#) = Straight
- ? [Grade](#) = Professional
- ? Crimp Type = Hex
- ? Body Material = Brass
- ? Dielectric Material = PTFE
- ? Sealed = No
- ? Isolated = No

Mechanical Attachment:

- ? [Panel Attachment](#) = Without

Electrical Characteristics:

- ? [Connector Impedance \(?\)](#) = 50
- ? Environmental Seal = Without

Termination Related Features:

- ? Coaxial Cable Termination Type = Solder/Crimp

Body Related Features:

- ? Coupler Style = Snap -On
- ? [Pin Protection](#) = Without
- ? Solder Lug = Without
- ? [Body Plating](#) = Gold
- ? Overall Length (mm [in]) = 16.10 [0.634]
- ? Polarized = No
- ? Hexcrimp Dimension = 0.65 Sq + 2.8 + 3.4
- ? Hand Tool No. = 9 -1478240 -0
- ? Interchangeable Die Set Number = 9 -1478248 -0
- ? Ferrule Type = Hex

Contact Related Features:

- ? [Center Contact Plating](#) = Gold
- ? Contacts = With
- ? Center Contact Material = Brass

Configuration Related Features:

- ? [Coaxial Cable Type \(RG/U or Mfg.\)](#) = 174A/U, 188A/U, 316/U, Raychem 5026A1318, Raychem 5026A1331, Raychem 5026A1631, Raychem 5026C1309, Raychem 5026D1028, Raychem 5026D1424, Raychem CLFH -316, Raychem EPD 26995Q, URM 95

Industry Standards:

- ? [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- ? [Lead Free Solder Processes](#) = Not relevant for lead free process
- ? RoHS/ELV Compliance History = Converted to comply with RoHS directive

Conditions for Usage:

- ? [Terminate To](#) = Coaxial Cable
- ? Operating Temperature (Max.) (°C) = 165

Packaging Related Features:

- ? Packaging Quantity = 100
- ? Packaging Method = Individual

Other:

- ? Brand = Greenpar