

**1 - 1337499 - 0 Product Details**

**Live Product Chat** US Only  
8:30am - 5pm ET, Mon - Fri



**BNC RF Connectors**

[Converted to EU RoHS/ELV Compliant](#) ( [Statement of Compliance](#) )

**Product Highlights:**

- ? Connector
- ? Connector Type = BNC
- ? Jack
- ? Body Style = Panel
- ? Not Surface Mountable

[View all Features](#) | [Find Similar Products](#)

**Quick Links**

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

**1 - 1337499 - 0**

[Active](#)

**Documentation & Additional Information**

- Product Drawings:**
- ? [BNC PANEL SOCKET 50 OHM](#) (PDF, English)
- Catalog Pages/Data Sheets:**
- ? None Available
- Product Specifications:**
- ? None Available
- Application Specifications:**
- ? None Available
- Instruction Sheets:**
- ? None Available
- CAD Files:**
- ? None Available

- Additional Information:**
- ? [Product Line Information](#)
- Related Products:**
- ? [Tooling](#)

[List all Documents](#)

**Product Features** (Please use the Product Drawing for all design activity)

- |   |  |
|---|--|
| <p><b>Product Type Features:</b></p> <ul style="list-style-type: none"> <li>? <a href="#">Product Type</a> = Connector</li> <li>? <a href="#">Connector Type</a> = BNC</li> <li>? <a href="#">Gender</a> = Jack</li> <li>? Body Style = Panel</li> <li>? <a href="#">Grade</a> = Professional</li> <li>? <a href="#">Body Material</a> = Brass</li> <li>? <a href="#">Sealed</a> = No</li> <li>? <a href="#">Isolated</a> = No</li> <li>? <a href="#">Dielectric Material</a> = PTFE</li> <li>? Number of Ports = 1</li> <li>? Solder Terminal = With</li> </ul> <p><b>Mechanical Attachment:</b></p> <ul style="list-style-type: none"> <li>? Surface Mountable = No</li> <li>? <a href="#">Panel Attachment</a> = With</li> <li>? <a href="#">Panel Attachment Method</a> = Flange</li> <li>? Panel Attachment Style = Rear Mount, Front Mount</li> <li>? Panel Cutout = 1 x 9.0 + 4 x 3.2 Front Mount, 1 x 12.0 + 4 x 3.2 Rear Mount</li> <li>? Flange Dimension [Sq.] (mm [in]) = 17.50 [0.689]</li> </ul> <p><b>Electrical Characteristics:</b></p> <ul style="list-style-type: none"> <li>? <a href="#">Connector Impedance (?)</a> = 50</li> <li>? Frequency = DC - 2 GHz</li> </ul> | <p><b>Body Related Features:</b></p> <ul style="list-style-type: none"> <li>? <a href="#">Hardware Included</a> = No</li> <li>? <a href="#">Body Plating</a> = Nickel</li> <li>? <a href="#">Polarized</a> = No</li> </ul> <p><b>Contact Related Features:</b></p> <ul style="list-style-type: none"> <li>? <a href="#">Center Contact Material</a> = Brass</li> <li>? <a href="#">Center Contact Plating</a> = Gold</li> </ul> <p><b>Industry Standards:</b></p> <ul style="list-style-type: none"> <li>? Government/Industry Qualification = No</li> <li>? <a href="#">RoHS/ELV Compliance</a> = RoHS compliant, ELV compliant</li> <li>? <a href="#">Lead Free Solder Processes</a> = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C</li> <li>? RoHS/ELV Compliance History = Converted to comply with RoHS directive</li> </ul> <p><b>Conditions for Usage:</b></p> <ul style="list-style-type: none"> <li>? Operating Temperature (Max.) (°C) = 165</li> </ul> <p><b>Packaging Related Features:</b></p> <ul style="list-style-type: none"> <li>? Packaging Method = Individual</li> <li>? Packaging Quantity = 50</li> </ul> <p><b>Other:</b></p> <ul style="list-style-type: none"> <li>? Brand = Greenpar</li> </ul> |
|---|--|