



BNC CONNECTORS



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

BNC Str PCB Skt 50Ohm Nickel P

SKT , STA

1-1337535-0

TE Internal Number: 1-1337535-0

Converted to EU RoHS/ELV Compliant

Applies To **Printed Circuit Board**

Panel Mount Retention **Without**

PCB Mount Retention **With**

PCB Termination Method **Solder Tail (Pin)**

Body Material **Brass**

Product Drawings

[BNC STRAIGHT PCB SOCKET 50 OHM](#)

PDF (TIFF AVAILABLE)
English

[BNC STRAIGHT PCB SOCKET 50 OHM](#)

PDF (TIFF AVAILABLE)
English

CAD Files

[3D PDF](#)

PDF
3D

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Product Environmental Compliance

TE Material Declaration

[MD_1-1337535-0_110720132348_dmtec](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Applies To

Printed Circuit Board

Sealed

No

RF Connector Type

BNC





| | | |
|----------------------------|---------------------------------|---------------------------|
| | Connector Style | Jack |
| | PCB Mounting Orientation | Vertical |
| | Dielectric Material | PTFE |
| | Isolated Ground | No |
| | Grade | Professional |
| | Product Type | Connector - RF |
| Configuration Features | Solder Terminal | With |
| | Number of Ports | 1 |
| Electrical Characteristics | 50 Ohm | Yes |
| | 75 Ohm | No |
| | Impedance (Ω) | 50 |
| Signal Characteristics | Frequency (GHz) | 4 |
| Body Features | Body Material | Brass |
| | Body Plating Material | Nickel |
| | Body Style | Straight |
| | Body Insulation | With |
| | Body Shape | Circular |
| Contact Features | Center Contact Material | Brass |
| | Center Contact Plating Material | Gold |
| Termination Features | PCB Termination Method | Solder Tail (Pin) |
| Mechanical Attachment | Panel Mount Retention | Without |
| | PCB Mount Retention | With |
| | Polarized | No |
| | Mounting Post Length | 4.5 mm [.177 in] |
| | Mounting Post Style | Straight |
| | Hardware Included | No |
| Dimensions | PCB Thickness (Recommended) | 3.2 mm [.126 in] |
| Packaging Features | Packaging Quantity | 50 |

Product Compliance

[Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

| SURFACE MOUNT RESISTORS | SURFACE MOUNT RESISTORS | SURFACE MOUNT RESISTORS | STANDARD CIRCULAR I/O CONNECTORS |
|---|---|---|--|
|  <p>CRG1206 1% 220K CRG1206F220K</p> <p>Save to List Find Similar Products</p> |  <p>3520 2R2 5% 3520R2JT</p> <p>Save to List Find Similar Products</p> |  <p>3521 22R 1% 2W 352122RFT</p> <p>Save to List Find Similar Products</p> |  <p>PLUG ASSY DTS26W25-24PA</p> <p>Save to List Find Similar Products</p> |