


Products



My Account

Innovation



Support Center

Home > Products > RF & Coax > Product Feature Selector > Product Details

Resources

1-1337548-0 Product Details

Industries



BNC RF Connectors

About TE


BNC RM BHJ Hex 500hm Nickel Pltd RG174A/

1-1337548-0 🥖

TE Internal Number: 1-1337548-0

Product Highlights View All

- · Connector RF
- Jack
- Connector Style = Jack
- nination Type = Crimp



Related Products

you're looking for? **Find Similar Products**

View Part in Product Feature Selector

Check for Tooling

Not quite the product

	 Connector Style = J Applies To Coaxial (Coaxial Cable Term
Documents Features	Compliance
Please Note: Use the Product Drawing for all	design activity
Product Type Features	
Product Type ?	Connector - RF
Gender	Jack
Grade ?	Professional
Sealed ?	No
Isolated ?	No
Dielectric Material ?	PTFE
Flats Dimension	16.0 A/F
Mechanical Attachment	
Surface Mountable	No
Hardware Included ?	No
Panel Mount Retention	With
Panel Mount Retention Type	Hex Nut
Panel Attachment Style	Rear Mount
Panel Cutout	12.0mm x 12.9mm D-Shape
Flange Dimension [A/F] (mm [in])	17.5 [0.689]
Hand Tool No.	9-1478240-0
Interchangeable Die Set Number	9-1478245-0
Electrical Characteristic	DS .
Connector Impedance (Ω)	50
Frequency	DC - 4 GHz
Termination Features	
Coaxial Cable Termination Type ?	Crimp
Crimp Type ?	Hex
Crimp Dimensions	1.75 + 4.75
Dimensions	
Panel Thickness (mm [in])	2.00 - 5.00 [0.078 - 0.197]
Body Features	
Body Style	Bulkhead
Body Material ?	Brass
Body Plating ?	Nickel
Polarized ?	No
Ferrule Type	Hex
Flange and Thread Material	Brass

Contact Features	
Center Contact Material ?	Brass
Center Contact Plating	Gold
Housing Footunes	
Housing Features	71.
Connector Style	Jack
Configuration Features	
Coaxial Cable Type (RG/U or Mfg.) ?	174A, 188A, 316, Raychem 5026A1318, Raychem 5026A1331, Raychem 5026A1631, Raychem 5026C1309, Raychem 5026D1028, Raychem 5026D1424, Raychem CLFH-316, Raychem EPD 26995Q, URM 95
Number of Ports	1
Industry Standards	
Government/Industry Qualification	No
RoHS/ELV Compliance	RoHS compliant, ELV compliant
Lead Free Solder Processes ?	Not relevant for lead free process
RoHS/ELV Compliance History	Converted to comply with RoHS directive
Environmental	
Operating Temperature (Max.) (°C)	165
Conditions for Usage	
Applies To ?	Coaxial Cable
Packaging Features	
Packaging Method	Individual
Packaging Quantity	50
Other	

Corporate Information

Lockwasher Material

Lockwasher Plating

Gasket Material

About TE Investors News Room

Supplier Portal

Careers Terms & Conditions

Privacy Policy Global Accessibility Statement **Quick Links** Distributor Inventory

Product Cross Reference Documents & Drawings Product Compliance Support Center

Brand

Customer Support Email or Chat With Us Find a Phone Number Knowledge Base Manage Your Account

Greenpar

Keep Me Informed









Nickel

Mild Steel

White Silicone Rubber