



Electronics

a vital part of your world

Find Answers:

Tuesday, 29 November, 2005

CATALOG

Cross Reference

- [Competitive Products](#)
- [Military Spec P/Ns](#)
- [Tyco Brand P/Ns](#)

- [Part Number Search](#)
- [Document Search](#)
- [Product Type Search](#)
- [Product Family Search](#)
- [Alphabetical Search](#)
- [RoHS/ELV Compliance & Alternates](#)
- [CAD Model Search](#)
- [Brand Search](#)
- [Tool Search](#)
- [Multiple Part Comparison](#)
- [Lead Free Solutions](#)
- [Help/Glossary](#)

[Home](#)

e-bulletin newsletter
SUBSCRIBE NOW!
 click here

Terminal Block Products

↳ **Terminal Block Connectors**

BUCHANAN 1-1546074-0 [Active](#)

Directive 2002/95/EC Compliant

[RoHS Compliant](#)

(Tyco Electronics P/N: 1-1546074-0)

[Search for Parts](#)

Document links for this part cannot be displayed. Your browser does not support inline frames or is currently configured not to display inline frames. Inline frames are supported in both Internet Explorer 5 and Netscape 6, as well as all later versions of these browsers.

Related Part Information		
General Information	eCommerce	Related Part Information
<ul style="list-style-type: none"> ↳ General Info ↳ Sales Info 	<ul style="list-style-type: none"> ↳ Pricing ↳ Product Availability 	<ul style="list-style-type: none"> ↳ Tooling

Photos & Line Drawings - The photographs and/or line drawings are representative images of a product for viewing purposes only.

[Product View](#)

Searchable Features:	
Brand:	Buchanan
RoHS/ELV Compliance:	RoHS compliant, ELV compliant
Lead Free Solder Processes:	Wave solder capable to 240°C, Wave solder capable to 265°C
Product Type:	Connector
Housing Color:	Black
Stacked:	No
Threaded Flange:	Without
Screw Flange:	Without
Number of Positions:	10
Connector Type:	Wire Receptacle
Centerline (mm [in]):	5.08 [0.200]

Other Properties:	
RoHS/ELV Compliance History:	Always was RoHS compliant
Wire Range (mm [AWG]):	12-30 AWG
Housing Material:	Polyamide 6.6
Flammability Rating:	UL 94V-0
Contact Material:	Brass
Contact Mating Area Plating:	Tin
Voltage (VAC):	250
Screw Material:	Brass
Screw Plating:	Nickel

Wire Entry Diameter (Solid Wire) (mm²):	0.03 – 2.50
Wire Entry Diameter (Stranded Wire) (mm²):	0.03 – 1.50
Wire Entry Angle:	35°
Interlock:	With
Mount Angle:	Vertical

[Copyright](#) and [Privacy Statement](#)
Visit [Tyco International Ltd.](#)

[[Products](#) | [Catalog](#) | [Brands](#) | [Industries](#) | [Commerce](#) | [Supplier](#) | [Contact Us](#) | [About](#) | [Home](#)]

•