




- ⚠ UL RATED 94V-0 THERMOPLASTIC, BLACK.
- ⚠ PHOSPHOR BRONZE PER QQ-B-750.
- ⚠ .000015 MIN GOLD ON LOCALIZED GOLD PLATE AREA, .000050 MIN TIN ON TERMINATION END, ALL OVER .000050 MIN NICKEL ON ENTIRE CONTACT.
- ⚠ POLARIZING FEATURE DOES NOT EXIST ON SAME END AS THE POSITION NUMBER 1 INDICATOR ON 10 AND 14 POSITION PRODUCT.



1.125	2.100	2.380	2.150	43	44	1-1658621-3
1.625	3.100	3.380	3.150	63	64	1-1658621-2
1.525	2.900	3.180	2.950	59	60	1-1658621-1
1.275	2.400	2.680	2.450	49	50	1-1658621-0
1.025	1.900	2.180	1.950	39	40	1658621-9
.875	1.600	1.880	1.650	33	34	1658621-8
.775	1.400	1.680	1.450	29	30	1658621-7
.675	1.200	1.480	1.250	25	26	1658621-6
.625	1.100	1.380	1.150	23	24	1658621-5
.525	.900	1.180	.950	19	20	1658621-4
.425	.700	.980	.750	15	16	1658621-3
.375	.600	.880	.650	13	14	1658621-2
.275	.400	.680	.450	9	10	1658621-1
E	D	C	B	A	NO OF POSN	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIN R SAMICK 22AUG03	tyco Electronics	Tyco Electronics Corporation Harrisburg, PA 17105-3608			
CHK C. ROHDE 22AUG03		RECEPTACLE ASSY. CENTER & MILITARY POLARIZATION, LEAD FREE, AMP-LATCH™ NOVO			
APVD M. WALMSLEY 22AUG03	NAME	SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
PRODUCT SPEC	108-40000	A1	00779	1658621	
APPLICATION SPEC	114-40005	WEIGHT			
4 PLC ANGLES ± .5°	CONTACTS: ⚠	CUSTOMER DRAWING	SCALE 4:1	SHEET 1 OF 1	REV B2