



1-2112041-1 Product Details

[Share](#) | [Print](#) | [Email](#)


1-2112041-1

Multiple Contact Point (MCP) & MCON Contact Systems

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Multiple Contact Point (MCP) Product Line
- Wire-to-Wire
- Applies To Wire/Cable
- Connector
- Housing

[View all Features](#)

Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

TE Internal Number: 1-2112041-1

Active

[View 3D PDF](#)

[Add to My Part List](#) | [Request Sample](#) | [Find Similar Products](#) | [Buy Product](#)

Documentation & Additional Information

- Product Drawings:**
- [26 POS, 1.5 / 2.8 / 5.8 MM, TAB HOUSING, SEALED 26 ... \(PDF, English\)](#)
- Catalog Pages/Data Sheets:**
- None Available
- Product Specifications:**
- None Available
- Application Specifications:**
- None Available
- Instruction Sheets:**
- None Available

- Related Products:**
- [Tooling](#)

CAD Files: (CAD Format & Compression Information)

- [2D Drawing \(DXF, Version B\)](#)
- [3D Model \(IGES, Version B\)](#)
- [3D Model \(STEP, Version B\)](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

- | | |
|--|---|
| <p>Product Type Features:</p> <ul style="list-style-type: none"> • Product Line = Multiple Contact Point (MCP) • Product Type = Connector • Connector Type = Housing • Wire/Cable Type = FLR (Thin Walled Cable) • Connector System = LEAVYSEAL • Termination Method to Wire/Cable = Crimp • Key Type = Standard • Sealed = Yes <p>Mechanical Attachment:</p> <ul style="list-style-type: none"> • Contact Retention = With • Contact Retention Type = Secondary Locking/Retainer • Mating Retention Type = Latching <p>Termination Features:</p> <ul style="list-style-type: none"> • Seal Type = Axial Seal, Peripheral <p>Dimensions:</p> <ul style="list-style-type: none"> • Mating Area Interface Dimensions (mm [in]) = 1.50 [.059], 2.79 [.110], 6.30 [.248] <p>Body Features:</p> <ul style="list-style-type: none"> • Cable Exit Angle = 90° • Mating Retention = With • Wire Type = Stranded • Seal Material = Silicone • Seal Color = Green, White • Used With = Mated with Cover <p>Contact Features:</p> <ul style="list-style-type: none"> • Contact Type = Tab | <p>Housing Features:</p> <ul style="list-style-type: none"> • Connector Style = Plug • Housing Material = PBT GF30 • Housing Color = Black • Mating Alignment = With • Mating Alignment Type = Keyed <p>Configuration Features:</p> <ul style="list-style-type: none"> • Number of Positions = 26 • Number of Sections = 1 • Number of Positions/Section = 2+12+12 <p>Industry Standards:</p> <ul style="list-style-type: none"> • RoHS/ELV Compliance = RoHS compliant, ELV compliant • Lead Free Solder Processes = Not relevant for lead free process • RoHS/ELV Compliance History = Always was RoHS compliant <p>Identification Marking:</p> <ul style="list-style-type: none"> • Keying = A <p>Conditions for Usage:</p> <ul style="list-style-type: none"> • Applies To = Wire/Cable <p>Operation/Application:</p> <ul style="list-style-type: none"> • Application Use = Wire-to-Wire <p>Packaging Features:</p> <ul style="list-style-type: none"> • Packaging Method = Box • Packaging Quantity = 84 <p>Other:</p> <ul style="list-style-type: none"> • Brand = TE Connectivity • Comment = Left Cable Outlet |
|--|---|

Corporate Information

- [About TE](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)
- [Terms & Conditions](#)
- [Privacy Policy](#)

Quick Links

- [Distributor Inventory](#)
- [Product Cross Reference](#)
- [Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

Customer Support

- [Email or Chat With Us](#)
- [Find a Phone Number](#)
- [Knowledge Base](#)
- [Manage Your Account](#)

Keep Me Informed

Receive TE News, Events & Technology Updates

