






.025 (0.64) series connectors

Receptacle Contact

Contact	Wire Range	Wire Ins. Diameter	Material/Finish	Part No.		Hand Tool No. (Instruction sheet)
				S.T.	L.P.	
.025 Receptacle, crimping type  Application specification: 114-5250-1	0.22-0.5mm ²	0.95-1.7mm	Copper Alloy/Pre-tin	1123343-1	1318143-1	1463260-1 (411-5981)
			Copper Alloy/Sel. Gold	1123343-2	1318143-2	
.025 Receptacle, IDC type  Application specification: 114-5276-1	0.3-0.5mm ²	1.1-1.35mm	Copper Alloy/Post-tin	1318688-1	—	—
.025 Receptacle, IDC type  Application specification: 114-5276-1	0.08-0.14mm ²	1.1-1.4mm	Copper Alloy/Post-tin	1565403-1	—	—
	0.22mm ²	0.8-1.2mm	Copper Alloy/Post-tin	1565404-1	—	—

Tab Contact

Contact	Wire Range	Wire Ins. Diameter	Material/Finish	Part No.		Hand Tool No. (Instruction sheet)
				S.T.	L.P.	
.025 Tab, crimping type  Application specification: 114-5291-1	0.22-0.5mm ²	0.95-1.7mm	Brass/Pre-tin	1376109-1	1376607-1	1463260-1 (411-5981)
			Brass/Sel. Gold	1376109-2	1376607-2	
.025 Tab, IDC type  Application specification: 114-5276-1	0.08-0.14mm ²	1.1-1.4mm	Copper Alloy/Post-tin	1473818-1	—	—
	0.22mm ²	0.8-1.2mm	Copper Alloy/Post-tin	1565406-1	—	—