



TECHNICAL DATA SHEET 1330-3300

www.tycoident.com

Document number: TTDS-078 Issue: 2 Date: July 2006

Thermal Transfer Ribbons

| MATERIAL DESCRIPTION: | Black thermal transfer ribbon, recommended for use on Tyco Supplied Tedlar labels. On Tedlar this ribbon offers superior resistance To abrasion, steam and high temperature. |
|--------------------------|--|
| APPLICABLE PRINTERS | T208M, T212M: T308S, T312S, T312M T408M: |
| PRODUCTS: | TTVF, PVF |
| SHELF LIFE: | 2 years when stored between -5°c (23F) and 40°c (104F) |
| COLOR: | Black. |
| DIMENSIONS: | 300m x 110mm (984' x 4.33") for 1330-3300-10 74m x 110mm (242' x 4.33") for 1330-3300-101TT |
| WINDING DIRECTION: | Ink side out |
| ORDERING INFORMATION: | 1330-3300-10 for all T300, T400, series printers 1330-3300-101TT for all T200 series printers |
| PRINT PERFORMANCE | See Individual product technical data sheets |

Page 1 of 1

Business locations:

- N America: + 1 650 361 3860 (West Coast)
- Germany: + 49 (0) 6074 89080
- UK: + 44 (0) 1495 244000 (Labels)
- Japan: + 81 (0) 44 900 5102

- N America: + 1 401 751 6505 (East Coast)
- France: + 33 (0) 476 099696
- The second secon
- Singapore: + 65 (0) 4866 151

All the above information, including illustrations, is believed to be reliable. Users, however, should independently evaluate the suitability of each product for their application. Tyco Electronics makes no warranties as to the accuracy or completeness of the information and disclaims any liability regarding its use. Tyco Electronics only obligations are those in the Standard Terms and Conditions of Sale for this product and in no case will Tyco Electronics be liable for any incidental, indirect or consequential damages arising from the sale, resale, use or misuse of the product. Tyco Electronics Specifications are subject to change without notice. In addition Tyco Electronics reserves the right to make changes in materials or processing, without notification to the Buyer, which do not affect compliance with any applicable specification.