

CRIMP WIRE PINS & TABS



✓ Active



PRODUCT DRAWING



3D PDF

TE CONNECTIVITY (TE)

SKT ASSY, SHUR, INS, 4 MM DIA, 22-16 AWG

SHUR-PLUG | SHUR-PLUG

141456-1

TE Internal Number: 141456-1 Alias ID: A10184-000, AMPS-0-0141456-1

Always EU RoHS/ELV Compliant

Terminal Style Shur-Plug Receptacle

Pin Diameter 3 mm [.1179 in]

Wire Insulation Diameter (Max) 3.3 mm [.13 in]

Heavy Duty No

Wire Size (AWG) 20 - 16



Product Drawings

DOUILLE ISOLEE POUR BROCHE DE 3 Mm

PDF (TIFF AVAILABLE)

English

DOUILLE ISOLEE POUR BROCHE DE 3 Mm

PDF (TIFF AVAILABLE)

English

CAD Files

Customer View Model

2D_DXF.ZIP English

3D PDF

PDF

Customer View Model

3D_IGS.ZIP

Customer View Model

3D_STP.ZIP English Please review product documents or contact us for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Barrel Type	Closed Barrel
	Wire/Cable Type	Regular Wire
	Insulated	Yes
	Insulated Wire Support	Yes
	Support Style	Insulation Support
Body Features	Plating Material	Tin
	Double Wire	No
	Sleeve Material	Copper
	Insulation Sleeve Material	Nylon
Contact Features	Terminal Style	Shur-Plug Receptacle
	Pin Diameter	3 mm [.1179 in]
	Terminal Orientation	Straight
Termination Features	Bullet Terminal	Without
Dimensions	Wire Insulation Diameter (Max)	3.3 mm [.13 in]
	Wire Size (AWG)	20 – 16
	Wire Size (mm²)	.5 – 1.31
	Overall Length	25 mm [.9825 in]
Operation/Application	Heavy Duty	No
Packaging Features	Packaging Method	Вох
	Packaging Quantity	1000
Other	Barrel Color	Red
Product Compliance	Statement of Compliance	

VIEW ALL PRODUCT COMPLIANCE

