Have a Question?

Chat with a Product Information Specialist

What can we help you find?

Email

Buy Product

Products Industries Resources **About TE My Account Innovation Support Center**

Request Sample

1658657-1 Product Details



1658657-1

TE Internal Number: 1658657-1 Active



Standard Cable Connectors

Always EU RoHS/ELV Compliant (Statement of

Product Highlights:

- Connector
- Product Series = HDP-20 (Crimp Snap)
- 15 Positions
- With Enclosure
- Shielded

View all Features

Add to My Part List

Quick Links

Share

- Pricing & Availability Search for Tooling
- View Mating Products (10)
- View Plug Kits (4)
- Product Feature Selector
- Contact Us About This Product

Print

Documentation & Additional Information

Product Drawings:

KIT, PLUG, SHIELDING ENCLOSURE, SIZE 2, 15 POSN, AMP... (PDF, English)

Catalog Pages/Data Sheets:

AMPLIMITE Subminiature D Connectors - Cable Connectors (PDF, English)

Product Specifications:

AMPLIMITE HDP-20 Subminiature D Connector With F Cri... (PDF, English)

Application Specifications:

• AMPLIMITE HDP-20 and Economy Crimp Snap Subminiature... (PDF, English)

- Shielding Hardware Kits w/AMPLIMITE hde-20 hdp-20 an... (PDF, English)
- Shielding Hardware Enclosure Kits with AMPLIMITE* HD... (PDF, English)
- Insertion/Extraction Tool 91285-1 and Replacement Ti... (PDF, English)

CAD Files: (CAD Format & Compression Information)

- 2D Drawing (DXF, Version O)
- 3D Model (IGES, Version O)
- 3D Model (STEP, Version O)

Additional Information: Product Line Information

Find Similar Products

Related Products:

- Mating Products (10)
- Plug Kits (4)

List all Documents Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Type = Connector
- Product Series = HDP-20 (Crimp Snap)
- Mating Connector Lock = With
- Mating Connector Lock Type = Jackscrews
- Shell Size = 2
- Shell Type = Full Metal Shell
- Grounding Indents = With
- Grade = Standard
- Enclosure Material = PVC
- Color = Electrodeposited Polyurethane, Black
- Shell Material = Steel
- Shield Material = Steel

Electrical Characteristics:

Shielded = Yes

Dimensions:

- Cable Insulation Diameter (mm [in]) = 4.83 9.53 [0.190 -0.375]
- Cable Diameter (Max.) (mm [in]) = 8.89 [0.350]

Body Features:

- Jackscrew Material = Zinc Alloy
- Shell Plating = Tin over Copper
- Shield Plating = Tin
- Insert Material = Thermoplastic

Contact Features:

• Contact Size = 20

Housing Features:

- Enclosure = With
- Connector Style = Plug
- Housing Material = Nylon
- UL Flammability Rating = UL 94V-0
- Housing Color = Black

Configuration Features:

- Number of Positions = 15
- Preloaded = No
- Pre-Assembled = No

Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Not relevant for lead free
- RoHS/ELV Compliance History = Always was RoHS compliant
- Insert Flammability Rating = UL 94V-0

Packaging Features:

- Packaging Method = Bulk
- Packaging Quantity = 100

Other:

- Comment = Plugs accept size 20 DF pin contacts.; Maximum cable diameter after jacket and braid removed.; There is a maximum Cable O.D. of 9.02 [.355] for Shielding Enclosure Expansion Tool 58241-4.

