

1838292-3 Product Details

[Share](#) [Print](#) [Email](#)



1838292-3

TE Internal Number: 1838292-3

 Active

 [View 3D PDF](#)

M8/M12 Connector System

 Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Cable Assembly
- Plug
- Single Ended Configuration
- Wire Size = 0.34 (22 AWG) mm² [AWG]
- With Environmental Protection

[View all Features](#)

Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

[Add to My Part List](#)

[Request Sample](#)

[Find Similar Products](#)

[Buy Product](#)

Documentation & Additional Information

Product Drawings:

- [M8 RIGHT ANGLED MALE CONNECTOR WITH STRAIN RELIEF 4 ...](#) (PDF, English)

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files: [\(CAD Format & Compression Information\)](#)

- [2D Drawing](#) (DXF, Version B)
- [3D Model](#) (IGES, Version B)
- [3D Model](#) (STEP, Version B)

[List all Documents](#)

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- [Product Type](#) = Cable Assembly
- [Connector Type](#) = Plug
- [Wire Size \(mm² \[AWG\]\)](#) = 0.34 (22 AWG)
- [Thread Size](#) = M8
- [Mount Angle](#) = Right Angle
- [LED](#) = Without

Dimensions:

- [Cable Length \(M \[ft\]\)](#) = 5.00 [16.404]

Body Features:

- [Cable Color](#) = Black
- [Connector Color](#) = Black
- [Insulation Material](#) = PVC
- [Wire Color](#) = Brown, White, Blue, Black

Configuration Features:

- [Configuration](#) = Single Ended
- [Environmental Protection](#) = With
- [Number of Positions](#) = 4
- [Shielded](#) = No

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process
- [RoHS/ELV Compliance History](#) = Always was RoHS compliant

Operation/Application:

- [Application](#) = Sensors

Packaging Features:

- [Packaging Quantity](#) = 20

Other:

- [Brand](#) = TE Connectivity

Corporate Information

[About TE](#)

[Investors](#)

[News Room](#)

[Supplier Portal](#)

Quick Links

[Distributor Inventory](#)

[Product Cross Reference](#)

[Documents & Drawings](#)

[Product Compliance Support Center](#)

Customer Support

[Email or Chat With Us](#)

[Find a Phone Number](#)

[Knowledge Base](#)

[Manage Your Account](#)

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION MARCH , 2006.



© COPYRIGHT 2006 BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
	B	ECR-07-010734	08/05/07	AM	FWK
	B1	ECR-10-015172	13AUG10	RK	JK

NOTES:

- ELECTRICAL DATA: CONTACT RESISTANCE: 10 mOhm MAX
INSULATION RESISTANCE: 100 MOhm MIN at 500VDC
CURRENT RATING: 5 AMPS
BREAKDOWN VOLTAGE: 500 VAC MIN PER MINUTE
- ENVIRONMENTAL: OPERATING TEMPERATURE: -20°C TO +80°C
SEALING REQUIREMENTS: IP67
- PROD SPEC: 108-3641
- PACKAGING: 107-3334
- FOR TECHNICAL DATA REFER TO YOUR LOCAL TYCO ELECTRONICS SALES OFFICE
- ALL DIMENSIONS ARE NOMINAL FOR REFERENCE ONLY UNLESS OTHERWISE STATED

ITEM	DESCRIPTION	MATERIAL	FINISH/COLOUR	QTY
1	SCREW NUT	ZINC DIE CAST	2.5µm NICKEL PLATED	1
2	CONNECTOR BODY	POLYURETHANE	BLACK	1
3	PIN CONTACT	BRASS	0.15µm GOLD OVER NICKEL	4
4	4 CORE CABLE (CORES 22AWG TO UL2464)	PVC JACKET UV RESISTANT	BLACK	1



OBSOLETE	10000	500 mm	M8 RIGHT ANGLED MALE CONNECTOR 10.0m CABLE	1838292-5
	7000	350 mm	M8 RIGHT ANGLED MALE CONNECTOR 7.0m CABLE	1838292-4
	5000	250 mm	M8 RIGHT ANGLED MALE CONNECTOR 5.0m CABLE	1838292-3
OBSOLETE	3000	150 mm	M8 RIGHT ANGLED MALE CONNECTOR 3.0m CABLE	1838292-2
	2000	100 mm	M8 RIGHT ANGLED MALE CONNECTOR 2.0m CABLE	1838292-1
	DIM A	TOL 'B'	DESCRIPTION	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN MANJUNATH.T.N 29MAR06	Tyco Electronics Corporation Bideford, UK, EX39 4HE	
DIMENSIONS: mm		CHK F.WHEELER-KING 07AUG06	NAME M8 RIGHT ANGLED MALE CONNECTOR WITH STRAIN RELIEF 4 POSITION, PVC CABLE	
TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± - 4 PLC ± - ANGLES ± -		APVD F.WHEELER-KING 07AUG06	PRODUCT SPEC - APPLICATION SPEC -	
MATERIAL -		FINISH -	SIZE A3	RESTRICTED TO -
		WEIGHT -	CAGE CODE 00779	DRAWING NO 1838292
		CUSTOMER DRAWING		SCALE NTS
		SHEET 1 OF 1		REV B1