

## **Coming Soon:**

 Stacked SFP+ cages (dual row)

#### **DESCRIPTION**

SFP+ extends the use of the Small Form-Factor Pluggable (SFP) interconnect up to 10 Gb/s. This system meets the performance requirements of SFF (Small Form-Factor) specification SFF-8431 and supports 8G Fibre Channel and 10G Ethernet applications. The SFP+ product family includes cages, connectors, and copper cable assemblies. Tyco Electronics also offers LC optical connectors and cable assemblies to link with SFP+ transceivers.

### **APPLICATIONS**

- Storage
- Servers
- Networking
- Switches
- Routers
- Hubs
- Network Interface Cards (NICs)

# **KEY FEATURES & BENEFITS**

- SFP+ interconnect system supports data rates of 10 Gb/s
- Connector designed to support 10Gb/s+ signal speeds, backward compatible with SEP
- Both EMI spring and gasket options for cages provide excellent shielding
- All cage configurations are offered with lightpipes for LED applications
- Heatsink optional for single port cages
- Cages are available for PCI card applications (one degree mounting angle)
- Cages accommodate belly-to-belly mounting
- Active and passive copper cable assemblies provide a cost-effective solution for short reach applications.

PCI-SIG, PCI Express, PCIe, PCI-X and Conventional PCI are trademarks or registered trademarks of PCI-SIG.

All other trademarks mentioned are the property of their respective owners.



### **PART NUMBERS**

### Cages with EMI springs



Description	Single port	1x2	1x4	1x6
Cage Assy w/Light Pipes	2007254-1	2007262-1	2007178-1	2007250-1
Cage Assy	2007198-1	2007263-1	2007132-1	2007251-1
Cage Assy w/PCI Heatsink	2007464-1	_	_	
Cage Assy w/SAN Heatsink	2007464-2	_	_	
Cage Assy w/Networking Heatsink	2007464-3	_	_	_

#### Cages with elastomeric gaskets



Description	1x2	1x4	1x6	
Cage Assy w/Light Pipes	2007180-1	2007093-1	2007169-1	
Cage Assy	2007181-1	2007135-1	2007170-1	

#### Cages for PCI applications

 One degree mounting angle to meet requirements of SFF-8075



Description	Solder	Press-Fit	
Cage Assy	2007194-1	2007215-1	
Cage Assy w/PCI Heatsink & Clip	2007193-1	2007277-1	

#### **Connectors**



Contact Plating	Part Number
0.76μm (30 min) gold	1888247-1
0.38μm (15 min) gold	1888247-2

#### **Dust plug (non-conductive)**

For uses in	Part Number	
Single port cages	1367147-1 or 1761394-1	
Ganged (multi-port) cages	1761394-1	
Dust plus 1761204 1 has parrow width	required for part density in general access	

Dust plug 1761394-1 has narrow width, required for port density in ganged cages.

#### **EMI** plug

- Part Number: 1888901-1
- Springs comply with SFF-8432 requirements for improved pluggable form-factor (IPF)



PCI-SIG, PCI Express, PCIe, PCI-X and Conventional PCI are trademarks or registered trademarks of PCI-SIG. All other trademarks mentioned are the property of their respective owners.

#### PART NUMBERS

#### **Direct Attach Copper Cables**

- Truly broadband operates from 500 Mb/s up to 10 Gb/s
- Cost effective solution over Fiber Optic for short reach applications
- Compatible with industry standard SFP cages
- Active or passive equalization
- Broad range of lengths available
- EMI shielding
- Hot swappable
- Other options include: custom cable lengths, cross-over cables and labeling



#### Type **Part Number** Description 2032237-1 0.5 meter SFP+ Cable Assembly 2032237-2 1 meter SFP+ Cable Assembly 2032237-3 2 meter SFP+ Cable Assembly Passive 2032237-6 5 meter SFP+ Cable Assembly 1-2032237-1 10 meter SFP+ Cable Assembly 15 meter SFP+ Cable Assembly 1-2032237-6 1 meter SFP+ Cable Assembly 2032757-1 2032757-5 5 meter SFP+ Cable Assembly 10 meter SFP+ Cable Assembly 1-2032757-0 Active 1-2032757-5 15 meter SFP+ Cable Assembly 2-2032757-0 20 meter SFP+ Cable Assembly

Note: Other cable lengths are available, please see Tyco Electronics Customer Drawing

# FOR MORE INFORMATION

Technical Documents:

Application Specification 114-13120 Product Specification 108-2331

Industry standards:

Cage and module definition: SFF-8432 Mating Interface and performance require-

ments: SFF-8083

Electrical Interface Specifications:

SFF-8431

Product Manager: Mike Walmsley

Phone: 717-985-2835 Fax: 1-717-985-2833

Email: mjwalmsl@tycoelectronics.com

Technical Support

Internet: www.tycoelectronics.com

USA: 1-800-522-6752 Canada: 1-905-470-4425 UK: 44-1908-574289 Japan: 81-44-844-8013

 $\ensuremath{\circledcirc}$  Copyright 2008 by Tyco Electronics Corporation.

TE LOGO and TYCO ELECTRONICS are trademarks.

PCI-SIG, PCI Express, PCIe, PCI-X and Conventional PCI are trademarks or registered trademarks of PCI-SIG.

All other trademarks mentioned are the property of their respective owners.

Dimensions are in millimeters with inches (if shown) in brackets.

For more information, see Pluggable Input / Output Solutions Catalog No.1773408-1, contact your Tyco Electronics sales engineer, call 1-800-522-6752, or visit our Website at: http://www.tycoelectronics.com.

Specifications subject to change.

4-1773449-5-PDF-CC&CE-2/08