

a vital part of your world

Text Search:

Wednesday, 11 January, 2006

CATALOG

Cross Reference

- [Competitive Products](#)
- [Military Spec P/Ns](#)
- [Tyco Brand P/Ns](#)

- [Part Number Search](#)
- [Document Search](#)
- [Product Type Search](#)
- [Product Family Search](#)
- [Alphabetical Search](#)
- [RoHS/ELV Compliance & Alternates](#)
- [CAD Model Search](#)
- [Brand Search](#)
- [Tool Search](#)
- [Multiple Part Comparison](#)
- [Lead Free Solutions](#)
- [Help/Glossary](#)

[Home](#)

e-bulletin newsletter
SUBSCRIBE NOW!
[click here](#)

Soft Shell Connectors

↳ 5mm (.197") Centerline, 600 V, 14 A max. (Metrimate)

AMP 211759-1 [Active](#)

Directive 2002/95/EC Compliant

[RoHS Compliant](#)

(Corporate P/N: 211759-1)

[CAD Geometry](#) | [Search for Parts](#)

Document links for this part cannot be displayed. Your browser does not support inline frames or is currently configured not to display inline frames. Inline frames are supported in both Internet Explorer 5 and Netscape 6, as well as all later versions of these browsers.

Related Part Information

| General Information | eCommerce | Related Part Information |
|---|--|---|
| <ul style="list-style-type: none"> ↳ General Info ↳ Sales Info ↳ Assembly Subcontractors | <ul style="list-style-type: none"> ↳ Pricing & Availability | <ul style="list-style-type: none"> ↳ Tooling |

Photos & Line Drawings - The photographs and/or line drawings are representative images of a product for viewing purposes only.

[Product Photo](#)

Searchable Features:

| | |
|------------------------------------|--|
| Brand: | AMP |
| RoHS/ELV Compliance: | RoHS compliant, ELV compliant |
| Lead Free Solder Processes: | Wave solder capable to 240°C, Wave solder capable to 265°C |
| Product Type: | Housing |
| Connector Configuration: | Drawer |
| Drawer Style: | Standard |
| Number of Positions: | 12 |
| Gender: | Receptacle |
| Coaxial Socket: | Without |
| Keyed: | No |
| Mount: | Panel Mount |
| Mounting Ears: | Without |
| Centerline (mm [in]): | 5.08 [0.200] |
| Mating Connector Lock: | Without |
| 8/32 Insert: | No |
| PCB Retention Feature: | No |

Other Properties:

| | |
|-------------------------------------|--|
| RoHS/ELV Compliance History: | Always was RoHS compliant |
| Voltage (VAC): | 600 |
| Housing Material: | Glass-Filled Thermoplastic |
| Housing Color: | Black |
| Housing Flammability Rating: | UL 94V-0 |
| Comment: | Grounding Pins should not be used in 1 and 12 receptacle cavities. |

[Copyright and Privacy Statement](#)
Visit [Tyco International Ltd.](#)

[[Products](#) | [Catalog](#) | [Brands](#) | [Industries](#) | [Commerce](#) | [Supplier](#) | [Contact Us](#) | [About](#) | [Home](#)]