

TERMINALS





✓ Activ



PRODUCT DRAWING



3D PDF

TE CONNECTIVITY (TE)

GET MALE TERM, B, AU

AMP | Get .64 Connector System

2-1419158-3

TE Internal Number: 2-1419158-3

Always EU RoHS/ELV Compliant

Terminal Style Pin/Tab

Mating Tab Width 1 mm [.025 in]

Mating Tab Thickness .64 mm [.024 in]

Terminal Transmits 0 – 24 A (Low Power)

Wire Size Search (mm²) .5, .6, .75

Wire Size Search (AWG) 18, 19, 20

Product Drawings

0.64mm GET MALE IN-LINE TERMINAL

PDF **English**

CAD Files

Customer View Model

2D_DXF.ZIP English

3D PDF

PDF **3D**

Customer View Model

3D_IGS.ZIP English

Customer View Model

3D_STP.ZIP **English**

Product Specifications

Application Specification Global Electronic Technology (GET) 0.64-Mm Pin And Socket Terminals For GET

Connectors

PDF **English**

Instruction Sheets

Instruction Sheet (U.S.) Repositioning The TPA Of Unsealed GET Market Connectors

PDF **English**

Please review product documents or contact us for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

	Wire Type	Copper
Contact Features	Terminal Style	Pin/Tab
	Mating Tab Width	1 mm [.025 in]
	Mating Tab Thickness	.64 mm [.024 in]
	Interface Plating	Gold (Au)
	Typical Current Rating (A)	11
	Contact Termination Area Plating Material	Gold (Au)
Termination Features	Termination Method	Double Crimp
	Crimp Type	F-Crimp
Dimensions	Wire Size Search (mm²)	.5, .6, .75
	Wire Size Search (AWG)	18, 19, 20
	Wire Size	.5 – .75 mm² [20 – 18 AWG]
	Wire Insulation Diameter	1.4 – 2.06 mm [.055 – .081 in]
Usage Conditions	Operating Temperature (Max) (°C)	80, 85, 90, 100, 105, 110, 120, 125, 130, 140, 145, 150
	Operating Temperature (Max) (°F)	176, 185, 194, 212, 221, 230, 248, 257, 266, 284, 293, 302
	Operating Temperature Range	-40 – 150 °C [-40 – 302 °F]
Industry Standards	Agency/Standard	SAE/USCAR-2, USCAR-21
Other	Terminal Transmits	0 – 24 A (Low Power)
Product Compliance	Statement of Compliance PDF	
	VIEW ALL PRODUCT COMPLIANCE	





PRODUCT - MATING PRODUCTS

Connectors - Automotive, Truck, Bus, & Off-Road Terminals

AMP | Get .64 Connector System

V23540X7000Y20GET-FEM TERM AU - 1393365-1

TE INTERNAL NUMBER: 1393365-1 ALIAS ID: V23540X7000Y 20, V23540X7000Y20

✓ Active

Always EU RoHS/ELV Compliant

Terminal Style Receptacle/Socket

Mating Tab Width 1 mm

Mating Tab Thickness .64 mm

Terminal Transmits 0 – 24 A (Low Power)

Wire Size Search .5 mm², .6 mm², .75 mm²

