


2-1546670-6 Product Details



2-1546670-6

TE Internal Number: 2-1546670-6



[Active](#)



[View 3D PDF](#)

Barrier Strips

 [Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

Product Highlights:

- Barrier Strip
- Barrier Style = Double Row, Dual Barrier
- Block Style = Flat
- 11.10 mm Centerline
- Vertical Mount Angle

[View all Features](#)

Documentation & Additional Information

Product Drawings:

- [DOUBLE ROW BARRIER STRIP W/ BINDING HD SCREW, .437 S...](#) (PDF, English)

Catalog Pages/Data Sheets:

- [1-1773458-2 BARRIER STRIPS QUICK REFERENCE GUIDE](#) (PDF, English)
- [BUCHANAN TERMINAL BLOCKS CATALOG - BARRIER STRIPS](#) (PDF, English)

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files: ([CAD Format & Compression Information](#))

- [2D Drawing](#) (DXF, Version L)
- [3D Model](#) (IGES, Version L)
- [3D Model](#) (STEP, Version L)

[List all Documents](#)

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- [Product Type](#) = Barrier Strip
- [Mount Angle](#) = Vertical
- Screw Material = Steel
- Screw Size = 6-32 x 1/4
- Mounting Ears = With

Mechanical Attachment:

- Screw Plating = Nickel
- Mounting Style = Open End Position

Electrical Characteristics:

- [Top Hardware](#) = Wire Clamp Combo Head
- Number of Levels = Single
- Current Rating (A) = 25
- Mounting Insert = Without

Body Related Features:

- [Barrier Style](#) = Double Row, Dual Barrier
- [Block Style](#) = Flat
- [Centerline \(in \[mm\]\)](#) = 0.4375 [11.10]
- Number of Positions = 26
- Length (mm [in]) = 307.60 [12.110]
- Block Material = Thermoplastic
- Block Color = Black
- Wire Range (mm [AWG]) = 0.30-2.00² [22-14]

Contact Related Features:

- Mounting Options = End Mounting Ears

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

Other:

- Brand = Buchanan
- Comment = Other options available upon request, consult our Product Information Center.