



EUROCARD CONNECTORS



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE) 48P.IEC-F FEM.CONN.

EUROCARD | Eurocard

2-166010-1

TE Internal Number: 2-166010-1
 Alias ID: AMPS-2-0166010-1, C30079-000

Always EU RoHS/ELV Compliant

Connector Style **Receptacle**

Applies To **Printed Circuit Board**

Mounting Angle **Vertical**

Number of Columns **16**

Row-to-Row Spacing (mm) **2.54**

Product Drawings

[48 POS. FEMALE RC CONN. ACC. TO DIN 41612, F.48F-CIM WITH MAXI TERMI POINT POSTS](#)

PDF (TIFF AVAILABLE)
English

[48 POS. FEMALE RC CONN. ACC. TO DIN 41612, F.48F-CIM WITH MAXI TERMI POINT POSTS](#)

PDF (TIFF AVAILABLE)
English

CAD Files

[3D PDF](#)

PDF
3D

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English




Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Connector Style	Receptacle
Applies To	Printed Circuit Board
Row-to-Row Spacing (mm)	2.54
DIN Level	I
Pre-Notched to Break Off	No

	Product Type	Connector
	Make First / Break Last	No
	Type	Type F
	Post Type	Termi-Point
	Connector Type	Connector Assembly
Configuration Features	Number of Columns	16
	Number of Positions	48
	Number of Rows	3
	Rows Loaded	Z, B, D
Body Features	Color	Gray
Contact Features	Contact Transmits (Typical)	Signal (Data)
	Contact Type	Socket
	Contact Base Material	Phosphor Bronze
	Contact Mating Area Plating Material	Gold
	Contact Termination Area Plating Material	Tin-Lead
	Contact Mating Area Plating Thickness (µm)	.76
Termination Features	Termination Post Length	26.01 mm [1.024 in]
	Interface Type	Eurocard/DIN 41612
Mechanical Attachment	Mounting Angle	Vertical
	Panel Mount Retention	Without
	Mating Alignment	Without
	Mating Retention	With
Housing Features	Housing Material	Polycarbonate GF
Dimensions	Tail Length (mm)	28
Industry Standards	UL Flammability Rating	UL 94V-2
Packaging Features	Packaging Method	Tray

CUSTOMERS ALSO BOUGHT

MULTICORE CABLE	CHASSIS PANEL MOUNT RESISTORS	BOARD-TO-BOARD JUMPERS & SHUNTS	POWER CONTACTS
			
44A1111-20-9-9 44A1111-20-9-9	HSA25 8R2 5% HSA258R2J	SHUNT LP W/HANDLE 2POS 15AU 881545-1	UNIV.M-N-L.SOCKET 926893-3
Save to List Find Similar Products	Save to List Find Similar Products	Save to List Find Similar Products	Save to List Find Similar Products