

6

В

А

AMP 4805 REV 31MAR2000

5

4

(P2)		(P1)
	12 AWG, GREEN OR BARE	
\geq	10 AWG, WHITE	
	10 AWG, GRAY	
	12 AWG, GREEN/YELLOW	
2	12 AWG, PINK	
	12 AWG, BLACK	
	12 AWG, RED	
	12 AWG, BLUE	



THIS DRAWING IS A COM DIMENSIONS: MM [INCHES] $\bigoplus \square$ ATERIAL - 3

	2 1					
LOC DIST REVISIONS						
		DATE	DWN	APVD		
		4.0144500.4.4				
	G ECO-14-003630	12MAR2014	JM	MS		
1	DIMENSIONS SHOWN ARE MAXIMUM UNLESS OTHERWISE SPECIFIED.					
2	CABLE ASSEMBLY IS WIRED PER WIRING DIAGRAM.					
ß	MATERIAL: CONNECTOR HOUSINGS – POLYCARBONATE, UL 94V–O, RATED, BLACK. STRAIN RELIEFS – CARBON STEEL WITH NICKEL PLATING 5.08 μ m [.000200] MINIMUM THICK. CONTACTS – COPPER ALLOY WITH SILVER PLATED STRIP 3.81 μ m [.000150] MINIMUM THICK.					
4	DIMENSION A SHALL BE MEASURED WITH Conduit in the relaxed position.					
<u>/5</u>	DESIGNATIONS IN PARENTHESES () ARE FOR REFERENCE ONLY.					
6	MANUFACTURING LOCATION, DATE COD Part number and length shall be stamped where indicated.					
7.	APPLICATION: AMPINNERGY TM modular distribution system, a manufactur wiring system.		ER			
8	USE GROUND WIRE INSPECTION WINDO VERIFY BONDING AND GROUNDING CONDUCTOR.	DW TC	I			

2336.80 - 2342.20 [92.00 - 93.00]	2-558057-9
2082.80 - 2108.20 [82.00 - 83.00]	2-558057-8
457.20 - 469.90 [18.00 - 18.50]	2-558057-7
6096.00 - 6172.20 [240.00 - 243.00]	2-558057-6
4572.00 - 4622.80 [180.00 - 182.00]	2-558057-5
3657.60 - 3708.40 [144.00 - 146.00]	2-558057-4
3048.00 - 3073.40 [120.00 -121.00]	2-558057-3
1524.00 - 1543.05 [60.00 -60.75]	2-558057-2
609.60 - 622.30 [24.00 - 24.50]	2-558057-1
1854.20 - 1905.00 [73.00 - 74.00]	2-558057-0
749.30 - 762.00 [29.50 - 30.00]	1-558057-9
7620.00 - 7696.20 [300.00 - 303.00]	1-558057-8
889.00 - 901.70 [35.00 - 35.50]	1-558057-7
1752.60 - 1771.65 [69.00 - 69.75]	1-558057-6
1892.30 - 1917.70 [74.50 - 75.50]	1-558057-5
1803.40 - 1822.45 [71.00 - 71.75]	1-558057-4
584.20 - 596.90 [23.00 - 23.50]	1-558057-3
1587.50 - 1606.55 [62.50 - 63.25]	1-558057-2
1447.80 - 1466.85 [57.00 - 57.75]	1-558057-1
1498.60 - 1517.65 [59.00 - 59.75]	1-558057-0
1193.80 - 1206.50 [47.00 - 47.50]	558057-9
1536.70 - 1555.75 [60.50 - 61.25]	558057-8
1231.90 - 1250.95 [48.50 - 49.25]	558057-7
1143.00 - 1155.70 [45.00 - 45.50]	558057-6
927.10 - 939.80 [36.50 - 37.00]	558057-5
838.20 - 850.90 [33.00 - 33.50]	558057-4
622.30 - 635.00 [24.50 - 25.00]	558057-3
533.40 - 546.10 [21.00 - 21.50]	558057-2
15240.00 - 15316.20 [600.00 - 603.00]	558057-1
A (MIN – MAX)	PART NO.
	Tyco Electronics Corporation
	Harrisburg, PA 17105-3608
TOLERANCES UNLESS OTHERWISE SPECIFIED: APVD 23APR2007 NAME F. LINCOLN CAE	BLE ASSEMBLY,
0 PLC \pm PRODUCT SPEC POW	IER TO POWER,
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	E, 2#10 NEUTRAL
4 PLC ± - SIZE CAGE CODE DRAWING NO	RESTRICTED TO
$\begin{array}{c c} FINISH \\ - \end{array} \\ \hline \\ \hline \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\$	
CUSTOMER DRAWING	SCALE 1:1 SHEET 1 OF 1 REV G

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: 2-558057-6