




MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

8P MOD 1 SHROUDED HEADER, ST, TIN PLTD

AMPMODU | AMPMODU

280612-1

TE Internal Number: 280612-1

Always EU RoHS/ELV Compliant

Applies To **Printed Circuit Board**

Connector Style **Plug**

Centerline **3.96 mm [.156 in]**

Number of Positions **8**

Header Type **Shrouded**

Product Drawings

[AMP MODU MODI STRAIGHT VERSION POST SUPPORT ASSY](#)

PDF
English

CAD Files

[3D PDF](#)

PDF
3D

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Applies To

Printed Circuit Board

Connector Style

Plug

PCB Mounting Orientation

Vertical

Connector Type

Header

Stabilizers

Without

Strain Relief

Without

Board Standoff


Without

	Profile	Standard
	Product Type	Connector
	Gasket	Without
Configuration Features	Number of Positions	8
	Number of Rows	1
	Keyed	No
	Selectively Loaded	No
Electrical Characteristics	Dielectric Withstanding Voltage	750 V
Body Features	Header Type	Shrouded
	Post Size (in)	.01
Contact Features	Contact Protection	With
	Contact Shape	Square
	Contact Type	Pin
	Contact Base Material	Brass
	Solder Tail Contact Plating Material	Tin
	Contact Mating Area Plating Material	Tin
	Contact Protection Type	Shrouded
Termination Features	Termination Post Length (mm)	3.3
	Termination End Plating Material	Tin
	Termination Method to PC Board	Through Hole
Mechanical Attachment	PCB Mounting Style	Through Hole
	PCB Mount Retention	Without
	Panel Mount Retention	Without
	Mating Alignment	With
	Mating Connector Lock	Without
	Mating Alignment Type	Polarization
Housing Features	Centerline	3.96 mm [.156 in]
	Housing Color	Green
	Housing Material	Polycarbonate GF

Dimensions	Shrouded End Dimension (in)	.045
	Mating Post Length	10 mm [.393 in]
Usage Conditions	Operating Temperature Range (°C)	-65 – 105
Industry Standards	UL Flammability Rating	UL 94V-0
	Approved Standards	CSA LR7189, UL E28476
Packaging Features	Packaging Quantity	250
	Packaging Method	Box/Carton
Product Compliance	Statement of Compliance PDF VIEW ALL PRODUCT COMPLIANCE	

CUSTOMERS ALSO BOUGHT


MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES



12P MOD 1 SHROUDED HEADER, ST, TIN PLTD
280614-1

[Save to List](#)
[Find Similar Products](#)

MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES



4P MOD 1 SHROUDED HEADER, ST, TIN PLTD
280610-1

[Save to List](#)
[Find Similar Products](#)

RP 2A 0.25W 75R 0.1% 25PPM 1K RL
1-2176091-2

[Save to List](#)
[Find Similar Products](#)

SURFACE MOUNT RESISTORS

SMW5 R10 5% SMW5R10JT

[Save to List](#)
[Find Similar Products](#)