



Electronics

a vital part of your world

Find Answers:

Saturday, 15 October, 2005

CATALOG

- Cross Reference
 - [Competitive Products](#)
 - [Military Spec P/Ns](#)
 - [Tyco Brand P/Ns](#)

- [Part Number Search](#)
- [Document Search](#)
- [Product Type Search](#)
- [Product Family Search](#)
- [Alphabetical Search](#)
- [RoHS/ELV Compliance & Alternates](#)
- [CAD Model Search](#)
- [Brand Search](#)
- [Tool Search](#)
- [Multiple Part Comparison](#)
- [Lead Free Solutions](#)
- [Help/Glossary](#)

[Home](#)

e-bulletin newsletter
SUBSCRIBE NOW!
 click here

AMPMODU

➔ .100 Inch Centerline-IDC/Crimp AMPMODU Housings & Contacts

AMP 2-87499-9 Active

Directive 2002/95/EC Compliant

RoHS Compliant

(Corporate P/N: 2-87499-9)

[CAD Geometry](#) | [Search for Parts](#)

Document links for this part cannot be displayed. Your browser does not support inline frames or is currently configured not to display inline frames. Inline frames are supported in both Internet Explorer 5 and Netscape 6, as well as all later versions of these browsers.

Related Part Information		
General Information	eCommerce	Related Part Information
<ul style="list-style-type: none"> ➤ General Info ➤ Sales Info ➤ Assembly Subcontractors 	<ul style="list-style-type: none"> ➤ Pricing ➤ Product Availability 	<ul style="list-style-type: none"> ➤ Tooling

Photos & Line Drawings - The photographs and/or line drawings are representative images of a product for viewing purposes only.

[Product Photo](#)

Searchable Features:	
Brand:	AMP
RoHS/ELV Compliance:	RoHS compliant, ELV compliant
Lead Free Solder Processes:	Not relevant for lead free process
Product Type:	Housing
Number of Positions:	16
Housing Type:	Receptacle
Number of Rows:	Single
Mating Connector Lock:	Without
Centerline, Matrix (mm [in]):	2.54 [.100]
Strain Relief:	Without
Mating Polarization:	No

Other Properties:	
Stamped:	Yes
Flame Retardant:	Yes
Housing Material:	Thermoplastic
Operating Temperature (°C):	-65 – +105
Voltage Rating (VAC):	250
Contact Current Rating (Amps.):	3
Termination Resistance (mΩ):	12
Insulation Resistance (MΩ):	5,000
Dielectric Withstanding Voltage (V):	750
Approved Standards:	UL E28476, CSA LR7189

Keyed:	No
Connector Series:	Mod IV
Housing Color:	Black

Housing Configuration:	Both Ends Closed
Comment:	Cavity identification, AMP, part number and date code stamped on housing where size permits. Strain reliefs are available and may be purchased separately. Contact Extraction/ Lance Reset Tool No. 843996-3.

[Copyright and Privacy Statement](#)
Visit [Tyco International Ltd.](#)

[[Products](#) | [Catalog](#) | [Brands](#) | [Industries](#) | [Commerce](#) | [Supplier](#) | [Contact Us](#) | [About](#) | [Home](#)]

