

## **HEADERS & RECEPTACLES**







**PRODUCT DRAWING** 



♣ 3D PDF

TE CONNECTIVITY (TE)

CT BOX HDR H SMT 7P O/TAPE BLA

AMP CT | AMP CT

292173-7

TE Internal Number: 292173-7

Always EU RoHS/ELV Compliant

Centerline 2 mm [.079 in]

Number of Positions 7

PCB Mounting Orientation Right Angle

PCB Mounting Style Surface Mount

Number of Rows 1

**Product Drawings** 

SMT TYPE POST HDR ASS'Y (H) WITH BOSS &TAIL TYPE (TE CT CONN. 2mm

PITCH)

PDF English

**CAD Files** 

3D PDF

PDF 3D

Customer View Model

2D\_DXF.ZIP English

**Customer View Model** 3D\_IGS.ZIP

English

**Customer View Model** 

3D\_STP.ZIP

English

Catalog Pages/Data Sheets

2.0MM\_AMP\_CT\_CONNECTOR\_SERIES\_QUICK\_REF\_GUIDE

PDF **English** 

**Product Specifications** 

**Product Specification** 

AMP COMMON TERMINATION (CT), CONNECTOR, 2mm PITCH, M/T TYPE,

LEAD FREE VERSION

TIF

Japanese

AMP COMMON TERMINATION (CT), CONNECTOR, 2mm PITCH, M/T TYPE,

**LEAD FREE VERSION** 

PDF Japanese

AMP COMMON TERMINATION (CT), CONNECTOR, 2mm PTICH, M/T TYPE,

**LEAD FREE VERSION** 

PDF **English** 

Please review product documents or contact us for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

| Product Type Features      | PCB Mounting Orientation                   | Right Angle                    |
|----------------------------|--|--------------------------------|
|                            | Product Type                               | Connector                      |
|                            | Connector Type                             | Header                         |
|                            | Shape                                      | Rectangular                    |
|                            | Connector System                           | Wire-to-Board                  |
|                            | Wire/Cable Type                            | Discrete Wire                  |
|                            | Strain Relief                              | Without                        |
|                            | Sealed                                     | No                             |
|                            | Connector Style                            | Header                         |
|                            | Applies To                                 | Printed Circuit Board          |
| Configuration Features     | Number of Positions                        | 7                              |
|                            | Number of Rows                             | 1                              |
|                            | Tail Orientation                           | Inline                         |
|                            | Backwall/Post Interruptions                | With                           |
| Electrical Characteristics | Operating Voltage                          | 125 VAC [ 125 VDC ]            |
| Body Features              | Header Type                                | Shrouded                       |
| Contact Features           | Contact Mating Area Plating Material       | Tin                            |
|                            | Contact Mating Area Plating Thickness      | 1 – 2 µm [ 39.37 – 78.73 µin ] |
|                            | Contact Termination Area Plating Thickness | 1 – 2 µm [ 39.37 – 78.73 µin ] |
|                            | Contact Shape                              | Round                          |
|                            | Contact Termination Area Plating Material  | Tin                            |
|                            | Contact Type                               | Pin                            |
|                            | Contact Transmits (Typical)                | Signal (Data)                  |
|                            | Contact Current Rating (A)                 | 4                              |
|                            | Contact Layout                             | Inline                         |
|                            | Contact Design                             | Round Post                     |
|                            | Contact Base Material                      | Brass                          |
| Termination Features       | Termination Method to PC Board             | Surface Mount                  |

| Mechanical Attachment | PCB Mounting Style          | Surface Mount               |
|-----------------------|-----------------------------|-----------------------------|
|                       | PCB Mount Alignment         | With                        |
|                       | Mating Retention            | Without                     |
|                       | PCB Mount Retention         | With                        |
|                       | PCB Mount Retention Type    | Solder Pads                 |
|                       | Contact Retention           | With                        |
|                       | Mating Alignment Type       | Polarization                |
|                       | Contact Retention Type      | Locking Lance               |
|                       | Panel Mount Retention       | With                        |
|                       | Mating Alignment            | With                        |
| Housing Features      | Centerline                  | 2 mm [ .079 in ]            |
|                       | Housing Color               | Black                       |
|                       | Housing Material            | 6T PA(GF)                   |
| Dimensions            | Mating Post Length          | 4.2 mm [ .165 in ]          |
|                       | PCB Thickness (Recommended) | .8 mm [ .031 – .063 in ]    |
|                       | Height                      | 5.8 mm [ .228 in ]          |
|                       | Wire/Cable Size (AWG)       | 28 – 22                     |
|                       | Width                       | 9 mm [ .354 in ]            |
|                       | Length                      | 15.8 mm [ .622 in ]         |
| Usage Conditions      | Operating Temperature Range | -40 – 221 °C [-40 – 105 °F] |
| Operation/Application | For Use With                | Printed Circuit Board       |
|                       | Internal/External           | Internal                    |
|                       | Pick and Place Cover        | Without                     |
| Industry Standards    | UL Flammability Rating      | UL 94V-0                    |
|                       | UL File Number              | E28476                      |
|                       | Agency/Standard             | CSA, UL                     |
|                       | CSA File Number             | LR 7189                     |
| Packaging Features    | Packaging Method            | Tape, Box                   |
|                       | Packaging Quantity          | 500                         |
|                       |                             |                             |

- .

#### VIEW ALL PRODUCT COMPLIANCE



View All

Compare 0/10



Relation Type

RELATIONSHIP

## **Mating Products**

Used to identify Mating Parts

See All Mating Products



#### PRODUCT - MATING PRODUCTS

Connectors - Wire-to-Board Connector Housings AMP CT I AMP CT

CT MT REC ASSY 7P GRAY - 2-179694-7 TE INTERNAL NUMBER: 2-179694-7

✓ Active

#### Always EU RoHS/ELV Compliant

Centerline 2 mm

Number of Positions 7

Number of Rows 1

Mating Retention Without

RELATIONSHIP

# Mating Products

Used to identify Mating Parts

See All Mating Products



#### PRODUCT - MATING PRODUCTS

Connectors - Wire-to-Board Connector Housings AMP CT | AMP CT

CT CRIMP-2 REC HSG 7P NATURAL - 179228-7 TE INTERNAL NUMBER: 179228-7

✓ Active

I ERNA

### Always EU RoHS/ELV Compliant

Centerline 2 mm

Number of Positions 7

Number of Rows 1

Mating Retention Without

RELATIONSHIP

# Mating Products

Used to identify Mating Parts

See All Mating Products



#### PRODUCT - MATING PRODUCTS

Connectors - Wire-to-Board Connector Housings AMP CT | AMP CT

CT CONN MT REC ASSY 7P - 173977-7

TE INTERNAL NUMBER: 173977-7

✓ Activ

### Always EU RoHS/ELV Compliant

Centerline 2 mm

Number of Positions 7

Number of Rows 1

Mating Retention Without

